



Test Report: (7223)129-0536

Report Date: June 13, 2023

Factory Company Name: DENBASSAN BASKI BOYA SAN. VE TIC. LTD. STI.

Factory Address: ORGANIZE SANAYI BOLGESI 1. KISIM FAHRI KARACA CAD. NO: 2/1 20330 HONAZ DENIZLI

Sampling Method & Description:

Sampling Method & Description:			
I001) Untreated wastewater	Composite		Red, Pink, Colorless Liquid
I002) Effluent	-		Not tested
I003) Sludge	-		Not tested
I004) Leachate	-		Not tested
I005) Incoming water	-		Not tested

Discharge Type: **Indirect Discharge without Pretreatment**

On-site ETP / Pretreatment: No Homgenization Tank & Holding Time: No

Discharge Destination: DENIZLI ORGANIZED INDUSTRIAL ZONE

Permit Validation Date: 01.02.2024

Conventional, Anions & Heavy Metals Overall Category: Meet discharge criteria ZDHC MRSL Parameters: Not detected

Sludge Parameters: Not applicable

Sample Pick Up Date: June 1, 2023 Sampler Number: C74D106817995

Test Period: June 2, 2023 to June 13, 2023

Parameter(s) exceeded maximum holding time: Not exceeded

Remark

The results of this report shall not be used for any regulatory compliance purposes.

Type of Process: **Textile** Average total industrial wastewater generated: **Equal or more than 15m3/day**

Sludge Disposal Pathway: Not applicable

Type of Sludge: Not applicable

General enquiry and invoicing:
Hasan Altingul
hasan.altingul@bureauveritas.com
90 212 494 35 35 - Ext: 360

Technical enquiry:
Sabiha Yazici
sabiha.yazici@bureauveritas.com
90 212 494 35 35 - Ext: 426

Report reviewed by:

Hasan Altingul, DEPUTY OPERATIONS MANAGER

Report approved by:

Sabiha Yazici, SCM Technical Lead

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Consumer Products Services, Inc.

Yalçın Koreş Caddesi No:22 Erdiñ Binaları A Blok 2. Kule 1. Kat 34209 Güneşli, İstanbul / Turkey

Tel:+90.212.494 35 35 Fax:+90.212.494 35 60

Website:cps.bureauveritas.com



Test Report: (7223)129-0536

Report Date: June 13, 2023

Result Summary - ZDHC MRSL Wastewater Parameters

Test Items	Untreated wastewater	Effluent	Incoming water
1A) AP and APEOs	ND	NR	NR
1B) Anti-Microbials & Biocides	ND		NR
1C) Chlorinated Parafins	ND		NR
1D) Chlorobenzenes and Chlorotoluenes	ND		NR
1E) Chlorophenols	ND		NR
1F) DMFa	ND		NR
1G) Dyes - Carcinogenic or Equivalent Concern	ND		NR
1H) Dyes - Disperse (Sensitising)	ND		NR
1I) Dyes - Navy Blue Colourant	ND		NR
1J) Flame Retardants	ND		NR
1K) Glycols / Glycol Ethers	ND		NR
1L) Halogenated Solvents	ND		NR
1M) Organotin Compounds	ND		NR
1N) Other / Miscellaneous Chemicals	ND		NR
1O) PFCs	ND		NR
1P) Phthalates	ND		NR
1Q) PAHs	ND		NR
1R) Restricted Aromatic Amines	ND		NR
1S) UV Absorbers	ND		NR
1T) VOC	ND		NR



Test Report: (7223)129-0536

Report Date: June 13, 2023

Result Summary - ZDHC Heavy Metals, Conventional and Anions Wastewater Parameters

Test Items	Untreated wastewater	Effluent	Incoming water
Antimony	NR		NR
Chromium (VI)	Meet		NR
Barium	NR		NR
Selenium	NR		NR
Tin	NR		NR
Arsenic	NA		NR
Total Chromium	NR		NR
Cobalt	NR		NR
Cadmium	Meet		NR
Copper	NR		NR
Lead	Meet		NR
Nickel	NR		NR
Silver	NR		NR
Zinc	NR		NR
Mercury	Meet		NR
pH			
Temperature difference			
E.coli			
Colour		NR	
Persistent Foam			
Wastewater Flowrate			
Ammonium-Nitrogen			
AOX			
BOD ₅			
COD			
DO			
Oil & Grease	NR		NR
Total Phenols / Phenol Index			
Total Chlorine			
TDS			
Total Nitrogen			
Total Phosphorus			
TSS			
Chloride			
Cyanide, total			
Sulfate			
Sulfide			
Sulfite			



Test Report: (7223)129-0536

Report Date: June 13, 2023

Result Summary - ZDHC Sludge Parameters

Test Items	Sludge	Leachate
Antimony	NR	NR
Arsenic		NR
Barium		NR
Cadmium		NR
Cobalt		NR
Copper		NR
Lead		NR
Nickel		NR
Selenium		NR
Silver		NR
Total Chromium		NR
Zinc		NR
Chromium (VI)		NR
Mercury		NR
Cyanide		NR
pH		
% Solids		
Paint Filter Test		
Fecal Coliform		
AP and APEOs		
PAHs		
Chlorotoluenes		

Note / Key:

Meet	=	Meet Foundational Limit / Meet Discharge Criteria
Not Meet	=	Exceed Foundational Limit / Exceed Discharge Criteria
NR	=	Not requested / Not required
NA	=	Not applicable
D	=	Detected
ND	=	Not detected
Refer to result	=	Legal parameter(s) and/or parameter(s) requested by factory, please refer to test result



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters

Test Parameters	Results of Test Items					Requirements [Textile]		
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -
1A) AP and APEOs: including all isomers								
NPEO	ND	NR	NR	NR	NR	5	0,4	-
NP, mixed isomers	ND				NR			
OPEO	ND				NR			
OP, mixed isomers	ND				NR			
1B) Anti-Microbials & Biocides								
o-Phenylphenol (+salts)	ND	NR	NR	NR	NR	100	-	-
Triclosan	ND				NR			
Permethrin	ND				NR			
1C) Chlorinated Parafins								
MCCPs (C14-C17)	ND	NR	NR	NR	NR	500	-	-
SCCPs (C10-C13)	ND				NR			
1D) Chlorobenzenes and Chlorotoluenes								
1,2-dichlorobenzene	ND	NR	NR	NR	NR	0,2	-	-
Other isomers of mono-, di-, tri-, tetra-, penta- and hexa- chlorobenzene	ND				NR			
Other isomers of mono-, di-, tri-, tetra- and penta- chlorotoluene	ND				NR			
1E) Chlorophenols								
2-chlorophenol	ND	NR	NR	NR	NR	0,5	-	-
3-chlorophenol	ND				NR			
4-chlorophenol	ND				NR			
2,3-dichlorophenol	ND				NR			
2,4-dichlorophenol	ND				NR			
2,5-dichlorophenol	ND				NR			
2,6-dichlorophenol	ND				NR			
3,4-dichlorophenol	ND				NR			
3,5-dichlorophenol	ND				NR			
2,3,4-trichlorophenol	ND				NR			
2,3,5-trichlorophenol	ND				NR			
2,3,6-trichlorophenol	ND				NR			
2,4,5-trichlorophenol	ND				NR			
2,4,6-trichlorophenol	ND				NR			
3,4,5-trichlorophenol	ND				NR			
2,3,5,6-tetrachlorophenol	ND				NR			
2,3,4,6-tetrachlorophenol	ND				NR			
2,3,4,5-tetrachlorophenol	ND	NR						
Pentachlorophenol (PCP)	ND	NR						
1F) N,N-di-methylformamide (DMFa)								
Dimethyl formamide; N,N-dimethylformamide (DMFa) ^a	ND	NR	NR	NR	NR	1000	-	-

a = Report only for mock leather

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters (continued)

Test Parameters	Results of Test Items					Requirements [Textile]		
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -
1G) Dyes - Carcinogenic or Equivalent Concern								
Basic violet 3 with >0.1% of Michler's Ketone	ND				NR	500	-	-
C.I. Acid Red 26	ND				NR			
C.I. Acid Violet 49	ND				NR			
C.I. Basic Blue 26 (with Michler's Ketone >0/1%)	ND				NR			
C.I. Basic Green 4 (Malachite Green Chloride)	ND				NR			
C.I. Basic Green 4 (Malachite Green Oxalate)	ND				NR			
C.I. Basic Green 4 (Malachite Green)	ND				NR			
C.I. Basic Red 9	ND	NR	NR	NR	NR			
C.I. Basic Violet 14	ND				NR			
C.I. Direct Black 38	ND				NR			
C.I. Direct Blue 6	ND				NR			
C.I. Direct Red 28	ND				NR			
C.I. Disperse Blue 1	ND				NR			
C.I. Disperse Blue 3	ND				NR			
Disperse Orange 11	ND				NR			
1H) Dyes - Disperse (Allergenic)								
Disperse Blue 102	ND				NR	50	-	-
Disperse Blue 106	ND				NR			
Disperse Blue 124	ND				NR			
Disperse Blue 26	ND				NR			
Disperse Blue 35 (CAS 12222-75-2)	ND				NR			
Disperse Blue 35 (CAS 56524-77-7)	ND				NR			
Disperse Blue 7	ND				NR			
Disperse Brown 1	ND				NR			
Disperse Orange 1	ND				NR			
Disperse Orange 3	ND	NR	NR	NR	NR			
Disperse Orange 37/59/76	ND				NR			
Disperse Red 1	ND				NR			
Disperse Red 11	ND				NR			
Disperse Red 17	ND				NR			
Disperse Yellow 1	ND				NR			
Disperse Yellow 3	ND				NR			
Disperse Yellow 39	ND				NR			
Disperse Yellow 49	ND				NR			
Disperse Yellow 9	ND				NR			
1I) Dyes - Navy Blue Colourant								
Component 1: C39H23Cl-CrN7O12S 2Na	ND				NR	500	-	-
Component 2: C46H-30CrN10O20S2 3Na	ND	NR	NR	NR	NR			

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters (continued)

Test Parameters	Results of Test Items					Requirements [Textile]		
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -
1J) Flame Retardants								
2,2-bis(bromomethyl)-1,3-propanediol (BBMP)	ND	NR	NR	NR	NR	25	-	-
Dis(2,3-dibromopropyl) phosphate (BIS)	ND				NR			
Decabromophenyl ether (DecaBDE)	ND				NR			
Hexabromocyclodecane (HBCDD)	ND				NR			
Octabromodiphenyl ether (OctaBDE)	ND				NR			
Pentabromodiphenyl ether (PentaBDE)	ND				NR			
Polybromobiphenyls (PBB)	ND				NR			
Tetrabromobisphenol A (TBBPA)	ND				NR			
Tris-(2-chloro-1-methylethyl) phosphate (TCPP)	ND				NR			
Tris(1-aziridinyl)phosphone oxide (TEPA)	ND				NR			
Tris(1,3-dichloro-isopropyl) phosphate (TDCP)	ND				NR			
Tris(2-chloroethyl) phosphate (TCEP)	ND				NR			
Tris(2,3-dibromopropyl) phosphate (TRIS)	ND				NR			
Decabromobiphenyl (DecaBB)	ND				NR			
Dibromobiphenyls (DiBB)	ND				NR			
Octabromobiphenyls (OctaBB)	ND				NR			
Dibromopropylether	ND				NR			
Heptabromodiphenyl ether (HeptaBDE)	ND				NR			
Hexabromodiphenyl ether (HexaBDE)	ND				NR			
Monobromobiphenyls (MonoBB)	ND				NR			
Monobromodiphenylethers (MonoBDEs)	ND				NR			
Nonabromobiphenyls (NonaBB)	ND				NR			
Nonabromodiphenyl ether (NonaBDE)	ND				NR			
Tetrabromodiphenyl ether (TetraBDE)	ND				NR			
Tribromophenylethers (TriBDEs)	ND				NR			
Boric acid ^b	ND				NR	100		
Diboron trioxide ^b	ND				NR			
Disodium octaborate ^b	ND				NR			
Disodium tetraborate anhydrous ^b	ND	NR						
Tetraboron disodium heptaoxide, hydrate ^b	ND	NR						
1K) Glycols / Glycol Ethers								
2-ethoxyethanol	ND	NR	NR	NR	NR	50	-	-
2-ethoxyethyl acetate	ND				NR			
2-methoxyethanol	ND				NR			
2-methoxyethylacetate	ND				NR			
2-methoxypropylacetate	ND				NR			
Bis(2-methoxyethyl)-ether	ND				NR			
Ethylene glycol dimethyl ether	ND				NR			
Triethylene glycol dimethyl ether	ND				NR			
1L) Halogenated Solvents								
1,2-dichloroethane	ND	NR	NR	NR	NR	1	-	-
Methylene chloride	ND				NR			
Tetrachloroethylene	ND				NR			
Trichloroethylene	ND				NR			

b = Limit refers to elemental boron, not the salt.

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters (continued)

Test Parameters	Results of Test Items					Requirements [Textile]								
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -						
1M) Organotin Compounds														
Dipropyltin compounds (DPT)	ND	NR	NR	NR	NR	0,01	-	-						
Mono, di-, and tri-butyltin derivatives	ND													
Mono, di-, and tri-methyltin derivatives	ND													
Mono, di-, and tri-octyltin derivatives	ND													
Mono, di-, and tri-phenyltin derivatives	ND													
Tetrabutyltin compounds (TeBT)	ND													
Tripropyltin compounds (TPT)	ND													
Tetraoctyltin compounds (TeOT)	ND													
Tricyclohexyltin (TCyHT)	ND													
Tetraethyltin compounds (TeET)	ND													
1N) Other / Miscellaneous Chemicals														
AEEA [2-(2-aminoethylamino)ethanol]	ND				NR				NR	NR	NR	500	-	-
Bisphenol A	ND	NR												
Thiourea	ND	NR												
Quinoline	ND	NR												
Borate, zinc salt ^c	ND	NR												
Silica (used in sand blasting) ^d	NR	NR												
1O) Perfluorinated and Polyfluorinated Chemicals (PFCs)														
Perfluorooctane sulfonate (PFOS) and related substances, Perfluorooctanoic acid (PFOA)	ND	NR	NR	NR	NR	0,01	-	-						
Perfluorooctanoic acid (PFOA) related substances	ND				NR									
1P) Phthalates - including all other esters of ortho-phthalic acid														
1,2-benzenedicarboxylic acid, di-C6-8 branched and linear alkyl esters, C7-rich (DIHP)	ND	NR	NR	NR	NR	10	-	-						
1,2-benzenedicarboxylic acid, di-C7-11 branched and linear alkyl esters (DHNUP)	ND													
Bis(2-methoxyethyl)phthalate (DMEP)	ND													
Butyl benzyl phthalate (BBP)	ND													
Di-cyclohexyl phthalate (DCHP)	ND													
Di-iso-decyl phthalate (DIDP)	ND													
Di-iso-octyl phthalate (DIOP)	ND													
Di-iso-butyl phthalate (DIBP)	ND													
Di-iso-nonyl phthalate (DINP)	ND													
Di-n-hexyl phthalate (DnHP)	ND													
Di-n-octyl phthalate (DNOP)	ND													
Di-n-pentylphthalates	ND													
Di-n-propyl phthalate (DPRP)	ND													
Di(ethylhexyl) phthalate (DEHP)	ND													
Dibutyl phthalate (DBP)	ND													
Diethyl phthalate (DEP)	ND													
Diisopentylphthalates	ND													
Dinonyl phthalate (DNP)	ND													

c = Limit refers to elemental boron and/or zinc, not the salt.

d = Not a ZDHC wastewater parameter, and not required to test this parameter as this is related to sand blasting

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters (continued)

Test Parameters	Results of Test Items					Requirements [Textile]		
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -
1Q) Polycyclic Aromatic Hydrocarbons (PAHs)								
Acenaphthene	ND	NR	NR	NR	NR	1	0,2	-
Acenaphthylene	ND							
Anthracene	ND							
Benzo[a]anthracene	ND							
Benzo[a]pyrene (BaP)	ND							
Benzo[b]fluoranthene	ND							
Benzo[e]pyrene	ND							
Benzo[ghi]perylene	ND							
Benzo[j]fluoranthene	ND							
Benzo[k]fluoranthene	ND							
Chrysene	ND							
Dibenz[a,h]anthracene	ND							
Fluoranthene	ND							
Fluorene	ND							
Indeno[1,2,3-cd]pyrene	ND							
Naphthalene	ND							
Phenanthrene	ND							
Pyrene	ND							
1R) Restricted Aromatic Amines (Cleavable from Azo-colourants)								
2-naphthylamine	ND	NR	NR	NR	NR	0,1	-	-
2-naphthylammoniumacetate	ND							
2,4-xylidine	ND							
2,4,5-trimethylaniline	ND							
2,4,5-trimethylaniline hydrochloride	ND							
2,6-xylidine	ND							
3,3'-dichlorobenzidine	ND							
3,3-dimethoxybenzidine	ND							
3,3-dimethylbenzidine	ND							
4-aminoazobenzene	ND							
4-aminodiphenyl	ND							
4-chloro-o-toluidine	ND							
4-chloro-o-toluidinium chloride	ND							
4-chloroaniline	ND							
4-methoxy-m-phenylene diammonium sulphate; 2,4-diaminoanisole sulphate	ND							
4-methoxy-m-phenylenediamine	ND							
4-methyl-m-phenylenediamine	ND							
4,4-methylene-bis-(2-chloro-aniline)	ND							
4,4-methylenedi-o-toluidine	ND							
4,4-methylenedianiline	ND							
4,4-oxydianiline	ND							
4,4-thiodianiline	ND							
5-nitro-o-toluidine	ND							
6-methoxy-m-toluidine	ND							
Benzidine	ND							
o-aminoazotoluene	ND							
o-anisidine	ND							
o-toluidine	ND							

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines. Bureau Veritas Consumer Products Services, Inc.

Yalçın Koreş Caddesi No:22 Erdiñ Binaları A Blok 2. Kule 1. Kat 34209 Güneşli, Istanbul / Turkey

Tel:+90.212.494 35 35 Fax:+90.212.494 35 60

Website:cps.bureauveritas.com



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC MRSL Parameters (continued)

Test Parameters	Results of Test Items					Requirements [Textile]		
	I001 (µg/L)	I002 (µg/L)	I003 [#] (mg/kg)	I004 [#] (mg/L)	I005 (µg/L)	Wastewater (µg/L)	Sludge [#] (mg/kg)	Leachate [#] -
1S) UV Absorbers								
2-(2H-benzotriazol-2-yl)-4-(tert-butyl)-6-(sec-butyl) phenol (UV-350)	ND	NR	NR	NR	NR	100	-	-
2-(2H-benzotriazol-2-yl)-4,6- ditertpentylphenol (UV-328)	ND				NR			
2-benzotriazol-2-yl-4,6-di-tert- butylphenol (UV-320)	ND				NR			
2,4-Di-tert-butyl-6-(5- chlorobenzotriazole-2-yl) phenol (UV-327)	ND				NR			
1T) Volatile Organic Compounds (VOC)								
Benzene	ND	NR	NR	NR	NR	1	-	-
m-cresol	ND				NR			
o-cresol	ND				NR			
p-cresol	ND				NR			
Xylene	ND				NR			
Toluene ^a	ND				NR			

a = Report only for mock leather

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC Heavy Metals Parameters

Test Parameters	Unit			Results of Test Items					Requirements [Textile]						
	Wastewater	Sludge	Leachate	I001	I002	I003#	I004#	I005	Wastewater			Sludge			
									Foundational	Progressive	Aspirational	Discharge Limit	Sludge Threshold Values		
ZDHC Heavy Metals															
Antimony	mg/L	mg/kg	mg/L	NR	NR	NR	NR	NR	0,1	0,05	0,01	-	12		
Chromium (VI)	mg/L	mg/kg	mg/L	ND				NR	0,05	0,005	0,001	0,5	50		
Barium	mg/L	mg/kg	mg/L	NR				Sample & Report	-	700					
Selenium	mg/L	mg/kg	mg/L	NR					-	10					
Tin	mg/L	-	-	NR					-	-					
Arsenic	mg/L	mg/kg	mg/L	ND				NR	0,05	0,01	0,005	Not Applicable	10		
Total Chromium	mg/L	mg/kg	mg/L	NR				NR	NR	NR	0,2	0,1	0,05	-	100
Cobalt	mg/L	mg/kg	mg/L	NR				NR	NR	NR	0,05	0,02	0,01	-	1600
Cadmium	mg/L	mg/kg	mg/L	ND				NR	NR	NR	0,1	0,05	0,01	0,1	3
Copper	mg/L	mg/kg	mg/L	NR				NR	NR	NR	1	0,5	0,25	-	200
Lead	mg/L	mg/kg	mg/L	ND				NR	NR	NR	0,1	0,05	0,01	1	10
Nickel	mg/L	mg/kg	mg/L	NR				NR	NR	NR	0,2	0,1	0,05	-	70
Silver	mg/L	mg/kg	mg/L	NR				NR	NR	NR	0,1	0,05	0,005	-	100
Zinc	mg/L	mg/kg	mg/L	NR				NR	NR	NR	5	1	0,5	-	1000
Mercury	mg/L	mg/kg	mg/L	ND	NR	NR	NR	0,01	0,005	0,001	0,1	1			

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Test Result - ZDHC Conventional and Anions Parameters

Test Parameters	Unit			Results of Test Items					Requirements [Textile]					
	Wastewater	Sludge	Leachate	I001	I002	I003#	I004#	I005	Wastewater			Discharge Limit	Sludge Threshold Values	
									Foundational	Progressive	Aspirational			
ZDHC Conventional														
pH	pH									6 - 9				
Temparture difference	Δ °C									15	10	5		
E.coli	MPN/100-ml									126				
Colour (436 nm)	m ⁻¹									7	5	2		
Colour (525 nm)	m ⁻¹									5	3	1		
Colour (620 nm)	m ⁻¹									3	2	1		
Persistent Foam	-									No indication of Persistent Foam				
Wastewater Flowrate	m ³ /day									-				
Ammonium-Nitrogen	mg/L									10	1	0,5		
AOX	mg/L									3	0,5	0,1		
BOD ₅	mg/L	-								30	15	8		
COD	mg/L			NR	NR	NR	NR	NR		150	80	40		
DO	mg/L									Sample & Report				
Oil & Grease	mg/L									10	2	0,5		
Total Phenols / Phenol Index	mg/L									0,5	0,01	0,001		
Total Chlorine	mg/L									Sample & Report				
TDS	mg/L									20	10	5		
Total Nitrogen	mg/L									3	0,5	0,1		
Total Phosphorus	mg/L									50	15	5		
TSS	mg/L													
% Solids	-	%												
Paint Filter Test	-	-												
Fecal Coliform	-	MPN/g												
ZDHC Anions														
Chloride	mg/L	-	-							Sample & Report				
Cyanide, total	mg/L	mg/kg	-							0,2	0,1	0,05		
Sulfate	mg/L			NR	NR	NR	NR	NR		Sample & Report				
Sulfide	mg/L	-	-							0,5	0,5	0,01		
Sulfite	mg/L									2	0,5	0,2		

#Limit refers to the chosen ZDHC sludge disposal pathway in Table 4 in accordance with the ZDHC Wastewater Guidelines.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix A - contract limit with CETP**Tablo 1. Denizli Organize Sanayi Bölge Müdürlüğü Merkezi Atıksu Arıtma Tesisi Tasarım Değerleri (Firmaların Kanalizasyona Deşarj Limitleri)***

SIRA NO	PARAMETRE	BİRİM	MİKTAR
1	Kimyasal Oksijen İhtiyacı (KOI)	mg/L	1.500
2	Biyokimyasal Oksijen İhtiyacı (BOİ ₅)	mg/L	350
3	Askıda Katı Madde (AKM)	mg/L	320
4	Yağ ve Gres	mg/L	60
5	Toplam Fosfor	mg/L	7
6	Toplam Krom	mg/L	1
7	Krom (Cr ⁺⁶)	mg/L	0,5
8	Kurşun (Pb)	mg/L	1
9	Toplam Siyanür (CN ⁻)	mg/L	0,5
10	Kadmiyum (Cd)	mg/L	0,1
11	Demir (Fe)	mg/L	5
12	Florür (F ⁻)	mg/L	5
13	Bakır (Cu)	mg/L	15
14	Çinko (Zn)	mg/L	3
15	Civa (Hg)	mg/L	0,10
16	Sülfat (SO ₄)	mg/L	2.000
17	Toplam Azot	mg/L	40
18	Balık Blyodeneği (ZSF)	---	---
19	Sıcaklık	°C	40
20	pH**	---	8,5-10,5

* Deşarj Limitleri ± %20-25 tolere edilebilir.

** : 2872 sayılı Çevre Kanunu'na bağlı Su Kirliliği Kontrolü Yönetmeliği deşarj standartlarına göre pH değeri 6 - 9 arası istenmektedir. Ancak yukarıda tabloda verilen pH değeri (8,5-10,5) ilk arıtma tesisi tasarımında kullanılan değerdir. Bu parametre değeri için minimum pH değeri 6 maksimum pH değeri 11 olması durumunda kanalizasyon şebekesinin işletilmesinde herhangi bir sorun teşkil etmeyeceğinden Bölge Müdürlüğümüzce pH= 6,0 - 11 kabul edilebilir sınırları içerisindedir.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix B - Sample Photos

I001) Sampling point

N/S 41° 10' 22.47" E/W 27° 29' 48.36"



I001) Sampling location surrounding

N/S 41° 10' 22.47" E/W 27° 29' 48.36"



I001) Labelled sample bottles



I001) Sample for phthalate test



I001) Sample packaging





Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix C - On-site Field Data Record Sheet

	FIELD DATA RECORD ON ZERO DISCHARGE SAMPLE (COMPOSITE / INDIVIDUAL SAMPLING)	CPSD-AN-00613-DATA 04 Issue Date: _____ Version No.: 17 Business Line: Analytical
--	---	--

General Data

Laboratory Sample Number: 72231290536

Client Name: DENBASSAN BASKI BOYA SANAYI VE TICARET LIMITED SIRKETI

Field Contact Person: NURSEL CINA Phone No:+902582691777

Project (Facility Name and Address): ORGANIZE SANAYI BOLGESI FAHRI KARACA CAD. NO: 2/1-3 1.KISIM HONAZ I DENIZLI

Sampling Location / Description: WASTEWATER BEFORE TREATMENT

Sample Identification: Zero discharge with sampling plan

Sample Type: Composite Sample / Grab sample (Please delete as appropriate)

Name of Sampler: Ali Seckin YILDIRIM

Discharge mode: Direct discharge to environment (Specify destination: River, Sea, Stream...) OR Indirect discharge to sewage treatment plant

Date of collection: 01.06.2023

Factory Type: Dyeing / Printing / Wearing / Finishing / Others (please specify): _____

*Note: It would be selected more than one

Field Data for Wastewater

Arrival Time	Departure Time:	
Field Parameters	pH: _____	Temp: _____ °C
Control No. of field equipment	Color: _____	Flow rate: (volume/min)
Factory with effluent treatment plant	Yes	No
Sample matrix	Incoming water (if required)	
	x Wastewater before treatment	
	Wastewater after treatment – water at discharge point	
Sampler container number	1	2
Recording time	ID	Time
	11:00	12:00
pH	7	8
Temp (°C)	21.1	24
Color (visual estimation)	red	pink
Flow rate (volume/time)	pink	pink
Volume collected, mL	red	red
Total volume collected	red	pink

Remark: Total volume collected must be greater than total of sample size required

Analysis Required and Preservation Method

Tests (ZDHC MRSL Parameters)	Test required (Y)	Total of sample size	Type of container	Preservation method		
Combined test or Individual test (Remark 4)	1. Phthalate	√	Amber Glass, washed with nitric acid.	Without adding acid Store sample at 2-8°C		
	2. Chlorobenzenes, Chlorotoluene & PAH	√				
	3. SCCPs	√				
	4. APS	√				
5. APEOs	√	100 mL				
6. Chlorophenols & Cresols	√	100 mL				
7. Flame retardant	√	500 mL				
8. Dyes	√	10 mL				
9. Glycol	√	50 mL				
10. *Pesticides		1000 mL				
11. *Nitrosamine		10 mL				
12. Banned Azodyes	√	2000 mL				
13. *Free primary aromatic amines		500 mL				
14. Organotin Compounds	√	500 mL				
15. UV absorbers	√	100				
16. BPA	√	2				
17. Preservatives	√	52				
18. VOC & Halogenated Solvents (Remark 6)	√	10 mL			PE, washed with pesticide grade Acetone	Fill to full container without air gap; acidify to pH 2 with HCl and store sample at 2-8°C
19. PFCs (Remark 6)	√	2 mL				Without adding acid Store sample at 2-8°C



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix C - On-site Field Data Record Sheet (continued)

	FIELD DATA RECORD ON ZERO DISCHARGE SAMPLE (COMPOSITE / INDIVIDUAL SAMPLING)	CPSD-AN-00613-DATA 04
		Issue Date:
		Version No.: 17
		Business Line: Analytical

Tests (Conventional Parameters)	Test required (V)	Total of sample size	Type of container	Preservation method
Combined test or Individual test (Remark 4) 20. Total suspended solids (TSS) 21. Total dissolved solids (TDS)		2000 mL total or 2000 mL each	Amber Glass, washed with nitric acid.	Without adding acid Store sample at 2-8°C
22. 5-day Biochemical Oxygen Demand (BOD5)		1000 mL		
23. Colour		100 mL		
24. Heavy Metals except Cr(VI) & Total-P (Remark 5)		9 mL	PE, washed with nitric acid	Acidify to pH 2 with HNO ₃ and store at 2-8°C
25. Cyanide		500 mL	Amber Glass, washed with pesticide grade acetone	Adjust pH 12 with 50% NaOH, add 0.05 ml of 10% Na ₂ S ₂ O ₅ and store sample at 2-8°C
26. Cr(VI)		95 mL		Filter by 0.45µm filter in field, fill to full container without air gap; adjust pH to 9.0-9.5 by adding ammonium buffer. Store sample at 2-8°C
27. Chemical oxygen demand (COD)		150 mL		
28. Phenols		500 mL	Amber Glass; washed with nitric acid	Acidify to pH 2 with H ₂ SO ₄ Store sample at 2-8°C
29. Oil and Grease & Total Hydrocarbon		1000 mL		
30. Formaldehyde		25 mL		Fill to full container without air gap; acidify to pH 2 with H ₂ SO ₄ and store sample at 2-8°C
31. Sulfide (Remark 5)		50 mL	PE, washed with pesticide grade Acetone;	Fill to full container without air gap; add 2 drops of 2M zinc acetate, adjust pH to 9 with 6M NaOH Store sample at 2-8°C
32. E coli (Remark 6)		125 mL	PE, clean, sterile, non-reactive	Add 0.1 ml of 10% Na ₂ S ₂ O ₅ ; keep in dark Store sample at 2-8°C
33. Persistent foam		N.A.	Foam higher than 45 cm (visual estimation): Yes / No	
34. Sulfite		100 mL	Amber Glass, washed with pesticide grade acetone	Add 1 mL of 2.5% EDTA Store sample at 2-8°C
35. Total-N		100 mL		Acidify to pH 2 with H ₂ SO ₄ Store sample at 2-8°C
36. Ammonium-N		500 mL		
37. Adsorbable organically bound halogens (AOX)		100 mL		Acidify to pH 2 with HNO ₃ and store at 2-8°C
38. Acute aquatic toxicity: Luminus Bacter a, Fish Egg, Daphnia: Algae;		1000 mL	Amber Glass washed with nitric acid;	
39. Sulphate		100 mL		Without adding acid Store sample at 2-8°C
40. Chloride		100 mL		
41. Conductivity		100 mL		
42. Dissolved oxygen (DO)		N.A.	measure in field	
43. Total Chlorine		N.A.		
44. Others:				

***Remarks:**

- Individual sampling can be performed upon request
- The minimum sampling time for 2019 ZDHC guideline is 6 hours with no more than one hour between discrete samples. Sampling time could be adjusted upon request.
- Scope of ZDHC guideline: Parameter 1-9, 12, 14-29, 31-37, 39-43
 Scope of synthetic leather industry: Parameter 1-9, 12, 14-24, 26-29, 31-33, 35, 36, 39, 40
 Scope of MMCF: Parameter 5, 18, 20, 22-24, 26-29, 31, 35-38
 Free primary aromatic amine, pesticides, nitrosamine and formaldehyde are not in the scope of ZDHC Guideline, they are tested upon request.
- Refer to CPSD-AN-G0019-STIPI01, locations with those CPSD test capability inside TCD matrix can perform the combined test.
- Refer to CPSD-AN-Q00570-MTHD for additional pretreatment of sulfide if only dissolved sulfide is required to be tested.
- Refer to CPSD-AN-00613-MTHD for preparation of field blank for specific parameters.

Recorded by: Ali Serkan YILDIRIM Date: 01.06.2023
 Full name:

Comment from factory: [Signature]



Signature of Factory Representative: [Signature] Date: 01.06.2023
 Full Name:



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater	Sludge		Wastewater	Sludge	
1A) AP and APEOs: including all isomers						
Nonylphenol ethoxylates (NPEO)	µg/L	mg/kg	9016-45-9, 26027-38-3, 37205-87-1, 68412-54-4, 127087-87-0	5	0,4	NP/OP: ISO 18857-2 (modified dichloromethane extraction) or ASTM D7065 (GC-MS or LC-MS(-MS), OPEO/NPEO (n>2): ASTM D7742 ISO 18857-2
Nonylphenol (NP), mixed isomers			104-40-5, 11066-49-2, 25154-52-3, 84852-15-3			
Octylphenol ethoxylates (OPEO)			9002-93-1, 9036-19-5, 68987-90-6			
Octylphenol (OP), mixed isomers			140-66-9, 1806-26-4, 27193-28-8			
1B) Anti-Microbials & Biocides						
o-Phenylphenol (+salts)	µg/L	-	90-43-7	100	-	USEPA 8270E Solvent extraction, derivatisation with KOH, acetic anhydride followed by GC-MS BS EN 12673-1999
Triclosan			3380-34-5			
Permethrin			Multiple	500		
1C) Chlorinated Paraffins						
Medium-chain chlorinated paraffins (MCCPs) (C14-C17)	µg/L	-	85535-85-9	500	-	EPA 3510 and analyzed by ISO18219-2:2021 Method for MCCP with GC-MS(NCI) or LC-MS/MS
Short-chain chlorinated paraffins (SCCPs) (C10-C13)			85535-84-8	25		
1D) Chlorobenzenes and Chlorotoluenes						
1,2-dichlorobenzene	µg/L	-	95-50-1	0,2	-	USEPA 8260D, 8270E, Purge and Trap, Head Space, Dichloromethane extraction followed by GC-MS
Other isomers of mono-, di-, tri-, tetra-, penta-, and hexa- chlorobenzene			Multiple			
Other isomers of mono-, di-, tri-, tetra-, and penta- chlorotoluene						
1E) Chlorophenols						
2-chlorophenol	µg/L	-	95-57-8	0,5	-	USEPA 8270E Solvent extraction, derivatisation with KOH, acetic anhydride followed by GC-MS, BS EN 12673-1999 the procedure of solvent extraction and derivatization are included
3-chlorophenol			108-43-0			
4-chlorophenol			106-48-9			
2,3-dichlorophenol			576-24-9			
2,4-dichlorophenol			120-83-2			
2,5-dichlorophenol			583-78-8			
2,6-dichlorophenol			87-65-0			
3,4-dichlorophenol			95-77-2			
3,5-dichlorophenol			591-35-5			
2,3,4-trichlorophenol			15950-66-0			
2,3,5-trichlorophenol			933-78-8			
2,3,6-trichlorophenol			933-75-5			
2,4,5-trichlorophenol			95-95-4			
2,4,6-trichlorophenol			88-06-2			
3,4,5-trichlorophenol			609-19-8			
2,3,5,6-tetrachlorophenol			935-95-5			
2,3,4,6-tetrachlorophenol			58-90-2			
2,3,4,5-tetrachlorophenol			4901-51-3			
Pentachlorophenol (PCP)			87-86-5			
1F) Dimethyl Formamide (DMFa)						
Dimethyl formamide; N,N-dimethylformamide (DMFa) ^a	µg/L	-	68-12-2	1000	-	EPA 8015, EPA 8270E

a = Report only for mock leather



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater	Sludge		Wastewater	Sludge	
1G) Dyes - Carcinogenic or Equivalent Concern						
Basic Violet 3 with >0.1% of Michler's Ketone	µg/L	-	548-62-9	500	-	Liquid extraction, LC-MS
C.I. Acid Red 26			3761-53-3			
C.I. Acid Violet 49			1694-09-3			
C.I. Basic Blue 26 (with Michler's Ketone > 0.1%)			2580-56-5			
C.I. Basic Green 4 (Malachite Green Chloride)			569-64-2			
C.I. Basic Green 4 (Malachite Green Oxalate)			2437-29-8			
C.I. Basic Green 4 (Malachite Green)			10309-95-2			
C.I. Basic Red 9			569-61-9			
C.I. Basic Violet 14			632-99-5			
C.I. Direct Black 38			1937-37-7			
C.I. Direct Blue 6			2602-46-2			
C.I. Direct Red 28			573-58-0			
C.I. Disperse Blue 1			2475-45-8			
C.I. Disperse Blue 3			2475-46-9			
Disperse Orange 11			82-28-0			
1H) Dyes - Disperse (Allergenic)						
Disperse Blue 102	µg/L	-	12222-97-8	50	-	Liquid extraction, LC-MS
Disperse Blue 106			12223-01-7			
Disperse Blue 124			61951-51-7			
Disperse Blue 26			3860-63-7			
Disperse Blue 35			12222-75-2			
			56524-77-7			
Disperse Blue 7			3179-90-6			
Disperse Brown 1			23355-64-8			
Disperse Orange 1			2581-69-3			
Disperse Orange 3			730-40-5			
Disperse Orange 37/59/76			13301-61-6			
Disperse Red 1			2872-52-8			
Disperse Red 11			2872-48-2			
Disperse Red 17			3179-89-3			
Disperse Yellow 1			119-15-3			
Disperse Yellow 3			2832-40-8			
Disperse Yellow 39			12236-29-2			
Disperse Yellow 49			54824-37-2			
Disperse Yellow 9	6373-73-5					
1I) Dyes - Navy Blue Colourant						
Component 1: C39H23Cl-CrN7O12S 2Na	µg/L	-	118685-33-9	500	-	Liquid extraction, LC-MS
Component 2: C46H-30CrN10O20S2 3Na			Not Allocated			



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater	Sludge		Wastewater	Sludge	
1J) Flame Retardants						
2,2-bis(bromomethyl)- 1,3-propanediol (BBMP)	µg/L	-	3296-90-0	25	-	USEPA 8270E, ISO 22032, USEPA 527 and USEPA 8321B Dichloromethane extraction GC-MS or LC-MS(-MS)
Bis(2,3-dibromopropyl) phosphate (BIS)			5412-25-9			
Decabromodiphenyl ether (DecaBDE)			1163-19-5			
Hexabromocyclodecane (HBCDD)			3194-55-6			
Octabromodiphenyl ether (OctaBDE)			32536-52-0			
Pentabromodiphenyl ether (PentaBDE)			32534-81-9			
Polybromobiphenyls (PBB)			59536-65-1			
Tetrabromobisphenol A (TBBPA)			79-94-7			
Tris-(2-chloro-1-methylethyl)phosphate (TCPP)			13674-84-5			
Tris(1-aziridinyl)phosphine oxide (TEPA)			545-55-1			
Tris(1,3-dichloro-isopropyl)phosphate (TDCP)			13674-87-8			
Tris(2-chloroethyl)phosphate (TCEP)			115-96-8			
Tris(2,3-dibromopropyl)-phosphate (TRIS)			126-72-7			
Decabromobiphenyl (DecaBB)			13654-09-6			
Dibromobiphenyls (DiBB)			Multiple			
Octabromobiphenyls (OctaBB)			Multiple			
Dibromopropylether			21850-44-2			
Heptabromodiphenyl ether (HeptaBDE)			68928-80-3			
Hexabromodiphenyl ether (HexaBDE)			36483-60-0			
Monobromobiphenyls (MonoBB)			Multiple			
Monobromodiphenylethers (MonoBDEs)			Multiple			
Nonabromobiphenyls (NonaBB)			63936-56-1			
Nonabromodiphenyl ether (NonaBDE)			40088-47-9			
Tetrabromodiphenyl ether (TetraBDE)			Multiple			
Tribromodiphenylethers (TriBDEs)			Multiple			
Boric acid ^b	10043-35-3, 11113-50-1	100	-	Determined as total boron via ICP		
Diboron trioxide ^b	1303-86-2					
Disodium octaborate ^b	12008-41-2					
Disodium tetraborate anhydrous ^b	1303-96-4, 1330-43-4					
Tetraboron disodium heptaoxide, hydrate ^b	12267-73-1					
1K) Glycols / Glycol Ethers						
2-ethoxyethanol	µg/L	-	110-80-5	50	-	USEPA 8270E Liquid extraction, LC-MS GC-MS
2-ethoxyethyl acetate			111-15-9			
2-methoxyethanol			109-86-4			
2-methoxyethylacetate			110-49-6			
2-methoxypropylacetate			70657-70-4			
Bis(2-methoxyethyl)-ether			111-96-6			
Ethylene glycol dimethyl ether			110-71-4			
Triethylene glycol dimethyl ether			112-49-2			
1L) Halogenated Solvents						
1,2-dichloroethane	µg/L	-	107-06-2	1	-	USEPA 8260D Headspace GC-MS or Purge and trap GC-MS
Methylene chloride			75-09-2			
Tetrachloroethylene			127-18-4			
Trichloroethylene			79-01-6			

b = Limit refer to elemental boron, not the salt.



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater	Sludge		Wastewater	Sludge	
1M) Organotin Compounds						
Dipropyltin compounds (DPT)	µg/L	-	Multiple	0,01	-	ISO 17353 Derivatisation with NaB (C2H5)4 GC-MS
Mono-, di- and tri-butyltin derivatives						
Mono-, di- and tri-methyltin derivatives						
Mono-, di- and tri-octyltin derivatives						
Mono-, di- and tri-phenyltin derivatives						
Tetrabutyltin compounds (TeBT)						
Tripopyltin Compounds (TPT)						
Tetraoctyltin compounds (TeOT)						
Tricyclohexyltin (TCyHT)						
Tetraethyltin Compounds (TeET)						
1N) Other/Miscellaneous Chemicals						
AEEA [2-(2-aminoethylamino)ethanol]	µg/L	-	111-41-1	500	-	Liquid extraction, LC-MSMS
Bisphenol A			80-05-7	10		
Thiourea			62-56-6	50		Liquid extraction, LC-MS
Quinoline			91-22-5	50		
Borate, zinc salt ^c			12767-90-7	100		Determine as total boron and total zinc via ICP
Silica (Used in sand blasting) ^d			14464-46-1	NA		Not a ZDHC Wastewater parameter
1O) Perfluorinated and Polyfluorinated Chemicals (PFCs)						
Perfluorooctane sulfonate (PFOS) and related substances, Perfluorooctanoic acid (PFOA)	µg/L	-	Multiple	0,01	-	PFCs: EPA 537:2020 FTOH: BS EN 12673-1999, EPA 8270 PFCs: LC-MSMS
Perfluorooctanoic acid (PFOA) related substances				1		FTOH: GC-MS Derivatisation with acetic anhydride followed by GC-MS
1P) Phthalates - including all other esters of ortho-phthalic acid						
1,2-benzenedicarboxylic acid, di-C6-8 branched and liearalkyl esters , C7-rich (DIHP)	µg/L	-	71888-89-6, 84777-06-0	10	-	USEPA 8270E, ISO 18856 Dichloromethane extraction GC-MS
1,2-benzenedicarboxylic acid, di-C7-11 branched and liearalkyl esters (DHNUP)			68515-42-4, 68515-50-4			
Bis(2-methoxyethyl)phthalate (DMEP)			117-82-8			
Butyl benzyl phthalate (BBP)			85-68-7			
Di-cyclohexyl phthalate (DCHP)			84-61-7			
Di-iso-decyl phthalate (DIDP)			26761-40-0			
Di-iso-octyl phthalate (DIOP)			27554-26-3			
Di-iso-butyl phthalate (DIBP)			84-69-5			
Di-iso-nonyl phthalate (DINP)			28553-12-0			
Di-n-hexyl phthalate (DnHP)			84-75-3			
Di-n-octyl phthalate (DNOP)			117-84-0			
Di-n-pentylphthalates			131-18-0			
Di-n-propyl phthalate (DPRP)			131-16-8			
Di(ethylhexyl) phthalate (DEHP)			117-81-7			
Dibutyl phthalate (DBP)			84-74-2			
Diethyl phthalate (DEP)			84-66-2			
Diisopentylphthalates			605-50-5			
Dinonyl phthalate (DNP)			84-76-4			

c = Limit refers to elemental boron and/or zinc, not the salt.

d = Not required to test this parameter as this is related to sand blasting



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods				
	Wastewater	Sludge		Wastewater	Sludge					
1Q) Polycyclic Aromatic Hydrocarbons (PAHs)										
Acenaphthene	µg/L	mg/kg	83-32-9	1	0,2	USEPA 8270E DIN 38407-39 Solvent extraction GC-MS				
Acenaphthylene			208-96-8							
Anthracene			120-12-7							
Benzo[a]anthracene			56-55-3							
Benzo[a]pyrene (BaP)			50-32-8							
Benzo[b]fluoranthene			205-99-2							
Benzo[e]pyrene			192-97-2							
Benzo[ghi]perylene			191-24-2							
Benzo[j]fluoranthene			205-82-3							
Benzo[k]fluoranthene			207-08-9							
Chrysene			218-01-9							
Dibenz[a,h]anthracene			53-70-3							
Fluoranthene			206-44-0							
Fluorene			86-73-7							
Indeno[1,2,3-cd]pyrene			193-39-5							
Naphthalene			91-20-3							
Phenanthrene			85-01-8							
Pyrene	129-00-0									
1R) Restricted Aromatic Amines (Cleavable from Azo-colourants)										
2-naphthylamine	µg/L	-	91-59-8	0,1	-	Reduction step with sodium dithionite, solvent extraction EPA 8270				
2-naphthylammoniumacetate			553-00-4							
2,4-xylidine			95-68-1							
2,4,5-trimethylaniline			137-17-7							
2,4,5-trimethylaniline hydrochloride			21436-97-5							
2,6-xylidine			87-62-7							
3,3'-dichlorobenzidine			91-94-1							
3,3-dimethoxybenzidine			119-90-4							
4-aminoazobenzene			60-09-3							
4-aminodiphenyl			92-67-1							
4-chloro-o-toluidine			95-69-2							
4-chloro-o-toluidinium chloride			3165-93-3							
4-chloroaniline			106-47-8							
4-methoxy-m-phenylene diammonium sulphate;			39156-41-7							
2,4-diaminoanisole sulphate			615-05-4							
4-methoxy-m-phenylenediamine			95-80-7							
4-methyl-m-phenylenediamine			101-14-4							
4,4-methylene-bis-(2-chloro-aniline)			838-88-0							
4,4-methylenedi-o-toluidine			101-77-9							
4,4-methylenedianiline			101-80-4							
4,4-thiodianiline			139-65-1							
5-nitro-o-toluidine			99-55-8							
6-methoxy-m-toluidine			120-71-8							
Benzidine			92-87-5							
o-aminoazotoluene			97-56-3							
o-anisidine			90-04-0							
o-toluidine			95-53-4							
										Reduction step with sodium dithionite, solvent extraction EPA 8270E and ISO 14362-1 GC/MS and LC/MS/MS



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater	Sludge		Wastewater	Sludge	
1S) UV Absorbers						
2-(2H-benzotriazol-2-yl)-4-(tert-butyl)-6-(sec-butyl) phenol (UV-350)	µg/L	-	36437-37-3	100	-	USEPA 8270 ISO 22032, USEPA 527 and USEPA 8321B. Dichloromethane extraction GC-MS or LC-MS(-MS)
2-(2H-benzotriazol-2-yl)-4,6- ditertpentylphenol (UV-328)			25973-55-1			
2-benzotriazol-2-yl-4,6-di-tert- butylphenol (UV-320)			3846-71-7			
2,4-Di-tert-butyl-6-(5- chlorobenzotriazole-2-yl) phenol (UV-327)			3864-99-1			
1T) Volatile Organic Compounds (VOC)						
Benzene	µg/L	-	71-43-2	1	-	ISO 11423-1 Headspace or Purge and trap GC-MS USEPA 8260D Add ISO 20595 Static headspace for determination of VOC in ISO 11423-1 Headspace or Purge and trap GC-MS EPA 8270 BS EN 12673-1999 ISO 11423-1 Headspace or Purge and trap GC-MS USEPA 8260D HJ 1067 or EPA 8260D or ISO 11423-1
m-cresol			108-39-4			
o-cresol			95-48-7			
p-cresol			106-44-5			
Xylene			1330-20-7			
Toluene ^a			108-88-3			

a = Report only for mock leather



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater & Leachate	Sludge		Wastewater	Sludge	
Heavy Metals						
Antimony	mg/L	mg/kg	7440-36-0	0,01	5	With reference to EPA 3015A, 6020A, 200.8, 6020B, 3051A and ISO 17294-2 and analyzed by ICP-MS With reference to EPA 1311 and HJ/T 300 for leachate
Chromium (VI)			18540-29-9	0,001	20	
Barium			7440-39-3	1	200	
Selenium			7782-49-2	1	5	
Tin			7440-31-5	1	-	
Arsenic			7440-38-2	0,005	5	
Total Chromium			7440-47-3	0,05	50	
Cobalt			7440-48-4	0,01	400	
Cadmium			7440-43-9	0,01	1	
Copper			7440-50-8	0,25	50	
Lead			7439-92-1	0,01	5	
Nickel			7440-02-0	0,05	20	
Silver			7440-22-4	0,005	50	
Zinc			7440-66-6	0,5	400	
Mercury			7439-97-6	0,001	1	
Conventional						
pH	pH	pH		6 - 9		With reference to ISO 10523, EPA 150.2, APHA 4500-H+
Temperature difference	°C			-		USEPA 170.1 or GB/T 13195
E.coli	MPN/100-ml			126		-
Colour	m ⁻¹			2;1;1		ISO 7887 (Method A and B)
Persistent Foam	-			-		-
Wastewater Flowrate	m ³ /day			-		-
Ammonium-Nitrogen	mg/L			0,5		ISO 11732, ISO 7150, USEPA 350.1, APHA 4500 NH ³ -N, HJ 535 or HJ 536
AOX	mg/L			0,1		ISO 9562, EN ISO 9563, USEPA 1650, HJ.T 83-2001
Biochemical Oxygen Demand 5-days concentration (BOD ₅)	mg/L			8		ISO 5815-1 & -2, EN1899-1, USEPA 405.1, APHA 5210B or HJ 505
Chemical Oxygen Demand (COD)	mg/L			40		ISO 6060, USEPA 410.4, APHA 5220D or GB/T 11914
Dissolved Oxygen (DO)	mg/L			-		ISO 5814, EPA 360.1 or HJ 506
Oil & Grease	mg/L			0,5		ISO 9377-2, USEPA 1664 or HJ 637
Total Phenols / Phenol Index	mg/L			0,001		ISO 14402, APHA 5530B, C, D or HJ 503
Total Chlorine	mg/L			0,1		ISO 7393-2, EPA 330.5 or HJ 586
Total Dissolved Solids (TDS)	mg/L			5		APHA 2540C, GB/T 5750.4
Total Nitrogen	mg/L			5		ISO 5663, ISO 29411, USEPA 351.2, APHA 4500P-J, APHA 4500N-C/ HJ 636 or GB 11891
Total Phosphorus	mg/L			0,1		ISO 11885, ISO 6878, USEPA 365.4, APHA 4500P-J or GB/T 11893
Total Suspended Solids (TSS)	mg/L			5		ISO 11923, USEPA 160.2, APHA 2540D or GB/T 11901
% Solids	-	%		-		USEPA 160.3, HJ 613
Paint Filter Test	-	-		-		EPA SW-846 or EPA 9095B
Fecal Coliform	-	bacteria/100m		-		EPA 1681



Test Report: (7223)129-0536

Report Date: June 13, 2023

Appendix D - Test methods, reporting limits and CAS numbers (continued)

Test Parameters	Unit		CAS No.	LOQ		Test methods
	Wastewater & Leachate	Sludge		Wastewater	Sludge	
Anions						
Chloride	mg/L	-	-	-	-	ISO 10304-1, ISO 15923-1, USEPA 300, HJ 84-2016, IS 3025 (part 32)
Cyanide, total		mg/kg		0,05	20	ISO 6703-1 & 2, ISO 14403-1 & 2, USEPA 335.2, APAH 4500-CN or HJ 484
Sulfate		-		-	-	ISO 10304-1, ISO 15923-1, USEPA 300, HJ 84-2016, IS 3025 (part 24)
Sulfide		-		0,01	-	ISO 10530, SM 4500-S2-D, E, G or I, GB/T 16489 or IS 3025 (part 29), HJ 1226-2021
Sulfite		-		0,2	-	ISO 10304-3, SM 4500-SO32-C or HJ 84-2016

END OF REPORT