



TEST REPORT

Technical Report / 技术报告

(6621) 320-0353

November 29, 2021

Date Received
收到时间:

November 16, 2021
2021 年 11 月 16 日

Page 1 of 33

Factory Company Name:

Jiangsu Pengcheng Group Dyeing & Finishing Co., Ltd

公司名称:

江苏彭城集团染整有限公司

Factory Address:

Qingshanquan Town, Jiawang District, Xuzhou City, Jiangsu Province

公司地址:

江苏省徐州市贾汪区青山泉镇

Project No.:

N/A

项目编号:

Client Reference No.:

N/A

客户编号:

Sample Type:

Wastewater - Time-Weighted Composite Grab Samples*

样品类型:

废水 - 加权复合取样

Sample Pick Up Date:

November 16, 2021

采样时间:

2021 年 11 月 16 日

Discharge Type:

Indirect Discharge

排放类型:

间接排放

Wastewater Discharge to:

Centralized ETP

废水排放去向:

集中污水处理设施

Off-site ETP name (if

applicable):

Town sewage treatment plant

外部污水处理厂名称

镇污水处理厂

Off-site ETP address (if

applicable):

Jiawang District, Xuzhou City, Jiangsu Province

外部污水处理厂地址

江苏省徐州市贾汪区

Local Regulation: / Ordinance /
requirements related to
wastewater discharged are
followed:

GB 4287-2012

当地法规: / 条例/需遵循的废
水排放相关要求

On-Site Effluent Treatment

Plant (ETP):

Yes

工厂内部污水处理设施:

是

Test Period:

November 16, 2021 to November 29, 2021

测试周期:

2021 年 11 月 16 日至 2021 年 11 月 29 日

Testing Option:

Option 3 – Incoming Water, Raw / Untreated Wastewater/ Treated Wastewater

测试选项:

选项 3 - 进水, 原始废水, 排放废水

Sample Description:

样品描述:

I001) Transparent liquid/透明液体– Incoming water/进水

I002) Light purple liquid/浅紫色液体– Raw, untreated wastewater/原始废水

I003) Light yellow liquid/浅黄色液体– Treated Wastewater/排放废水



Technical Report:

(6621)320-0353

November 29, 2020

Page 2 of 33

REMARK

If there are questions or concerns on this report, please contact the following persons:

若有任何疑问或咨询, 可通过下述联络方式与我们联系

General enquiry and invoicing

常规咨询和发票

Ms. Shelly Lin

林慧贤女士

(021)24081951

Shelly.Lin@bureauveritas.com

Technical enquiry-Chemical

化学技术问题

Mr. Steven Han

韩政先生

(021) 24081838

Steven-Z.han@bureauveritas.com

This report shown the test result of the auxiliary chemical and/or raw material samples, which collected during particular factory audit. The results of this report shall not be used for any regulatory compliance purposes.

此报告所示为特定工厂审核时收集的化学助剂和/或原材料样品的结果, 此报告的结果不得用于任何遵循法规的目的。

* The sampling is agreed with client.

采样已经过客户允许

BUREAU VERITAS

CONSUMER PRODUCTS SERVICES DIVISION (SHANGHAI)

必维申美商品检测(上海)有限公司

Laboratory Test Location 实验室检测地址:

No.368,Guangzhong Road, Zhuanqiao Town, Minhang, Shanghai.

上海市闵行区光中路 368 号

No.168, Guanghua Road, Zhuanqiao Town, Minhang, Shanghai.

上海市闵行区光华路 168 号

PREPARED BY: _____ Shelly

Steven Han 韩政
Technical Manager 技术经理

Executive Summary/执行摘要

1A) Conventional Parameters/常规参	I001	I002	I003
Temperature/温度	NR	NR	N/A
TSS/总悬浮固体			□
COD/化学需氧量			□
Total-N/总氮			□
pH Value/酸碱值			□
Color [m ⁻¹] (436nm; 525nm; 620nm)/色			N/A
BOD ₅ /五日生化需氧量			□
Ammonium-N/氨态氮			□
Total-P/总磷			□
AOX/可吸附有机卤化物			□
Oil and Grease/油和油脂			N/A
Phenol/苯酚			N/A
Coliform/大肠菌群			N/A
Persistent Foam /持泡性			N/A
ANIONS – Cyanide/阴离子-氰化物			N/A
ANIONS – Sulfide/阴离子 - 硫化物			□
ANIONS – Sulfite/阴离子 - 亚硫酸盐			N/A
1B) Conventional Parameters –METALS /常规参数 - 金属	N/A	N/A	N/A

Note / Key 注释 :

- – Meet Foundational Limit 符合基础限值/ Meet discharge license criteria 符合排放许可要求
- – Exceeding Foundational Limit 超出基础限值/ Exceeding discharge license criteria 超出排放许可要求
- NR – Not Requested 不需要/ Not required 不需要
- N/A – Not Applicable 不适用



Technical Report:

(6621)320-0353

November 29, 2020

Page 4 of 33

ZDHC MRSL Substances/ZDHC 生产限用物质清单	I001	I002	I003
2A) APs and APEOs/烷基酚及烷基酚聚氧乙烯醚	NR	o	o
2B) Chlorobenzenes and Chlorotoluenes/ 氯化苯和氯甲苯	NR	o	o
2C) Chlorophenols/氯酚	NR	o	o
2D) Azo Dyes/偶氮染料	NR	o	o
2E) Carcinogenic Dyes/致癌染料	NR	o	o
2F) Disperse Dyes/分散染料	NR	o	o
2G) Flame Retardants/阻燃剂	NR	o	o
2H) Glycols/乙二醇	NR	o	o
2I) Halogenated Solvents/卤化溶剂	NR	o	o
2J) Organotin Compounds/有机锡化合物	NR	o	o
2K) Perfluorinated and Polyfluorinated Chemicals/ 全氟化合物和多氟化合物	NR	o	o
2L) Phthalates/邻苯二甲酸盐	NR	o	o
2M) Poly Aromatic Hydrocarbons/多环芳香烃	NR	o	o
2N) Volatile Organic Compounds/挥发性有机化合物	NR	o	o

Note / Key 注释 :

- ● – Detected 检出
- o – Not Detected 未检出
- NR – Not Requested 不需要
- N/A – Not Applicable 不适用



Technical Report:

(6621)320-0353

November 29, 2020

Page 5 of 33

Objective/目标

The environment samples were tested for below parameters. 环境样品按照下列参数检测

- 1A) Conventional Parameters/常规参数
- 1B) Conventional Parameters – METALS/常规参数-重金属
- 2A) APs and APEOs/烷基酚及烷基酚聚氧乙烯醚
- 2B) Chlorobenzenes and Chlorotoluenes/氯化苯和氯甲苯
- 2C) Chlorophenols/氯酚
- 2D) Azo Dyes/偶氮染料
- 2E) Carcinogenic Dyes/致癌染料
- 2F) Disperse Dyes/分散染料
- 2G) Flame Retardants/阻燃剂
- 2H) Glycols/乙二醇
- 2I) Halogenated Solvents/卤化溶剂
- 2J) Organotin Compounds/有机锡化合物
- 2K) Perfluorinated and Polyfluorinated Chemicals/全氟化合物和多氟化合物
- 2L) Phthalates/邻苯二甲酸盐
- 2M) Poly Aromatic Hydrocarbons/多环芳香烃
- 2N) Volatile Organic Compounds/挥发性有机化合物

Sampling Plan

Basically, Three environment samples were sampled per factory, including 1) Incoming water ; 2) Raw, untreated wastewater and 3) Discharged Wastewater. Total number of sample collected will be depended on the actual factory facilities and manufacturing processes.

每个工厂需采集的样品主要有三种 1)进水；2) 原始废水和 3)排放废水。具体每种样品采集数量需根据工厂实际的生产设施和生产流程来决定。

Method of sampling used is time-weighted composite grab samples (agreed with client.). Composite sampling shall be performed for no less than six hours, with no more than one hour between discrete samples. Each discrete sample shall be of equal volume. Wastewater and freshwater samples should, as much as possible, be collected simultaneously, during the time that PU is in normal operation. The sampling shall aim to analyse the snapshot of water quality characteristics of the operating PU. Under no circumstance shall samples be taken during times when the production process is not running or the wastewater is diluted due to heavy rainfall, etc.

采样方法是时间加权复合抓取采样方法(经客户同意)。混合采样时间应不低于 6 小时，且每次取样的间隔不超过 1 小时。每次取样应保持在同一体积。污水和进水样品应尽可能同时采集，在此期间工厂应处于正常运行状态。采样的目的是为了看到工厂在实际运行状态下水质的特点。而当处于生产流程没有运行或废水被大雨所稀释等情况下时不应采集样品。

Remark 备注:

- Sampling procedure is with reference to below standards 采样流程参考如下标准:
 - 1) South Australia EPA Guidelines (June 2007), Regulatory Monitoring and Testing Water and Wastewater Sampling.
 - 2) Australia EPA (Victoria) Guideline (June 2009), Sampling and Analysis of Waters, Wastewaters, Soils and Wastes.
 - 3) ISO 5667-3:2003, Water Quality - Sampling - Part 3: Guidance on the Preservation and Handling of Water Samples.
 - 4) ASTM D3976-92 (Reapproved 2010), Standard Practice for Preparation of Sediment Samples for Chemical Analysis.
- Field data records are attached in Appendix C



Technical Report:

(6621)320-0353

November 29, 2020

Page 6 of 33

Test Result/测试结果

1A) Conventional Parameters/常规参数

Temperature/温度

Test Method : Measurement by thermometer GB/T 13195
测试方法 : 由温度计测量 GB/T 13195

Tested Item(s)	Result	Unit	Conclusion
I003	19.9	deg. C/ 摄氏度	DATA/数据

Note/注释:

deg. C = degree Celsius (°C)/摄氏度
Discharge License Criteria/排放标准: N/A

Total Suspended Solids (TSS)/ 总悬浮固体

Test Method : Reference to GB/T 11901
测试方法 : 参考 GB/T 11901

Tested Item(s)	Result	Unit	Conclusion
I003	6 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤100

Chemical Oxygen Demand (COD)/ 化学需氧量

Test Method : Reference to HJ828-2017
测试方法 : 参考 HJ828-2017

Tested Item(s)	Result	Unit	Conclusion
I003	63 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤200



Technical Report:

(6621)320-0353

November 29, 2020

Page 7 of 33

Total Nitrogen (Total-N)/总氮

Test Method : Reference to HJ 636
测试方法 参考 HJ 636

Tested Item(s)	Result	Unit	Conclusion
I003	7.32 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升

Discharge License Criteria/排放标准: ≤30

pH Value/酸碱值

Test Method : Reference to GB/T 6920
测试方法 参考 GB/T 6920

-	Unit	Result
Test Item(s)	-	I003
Parameter	-	-
Temp. of sample	deg. C	18.4
pH value of sample	-	7.8 Meet discharge license criteria 符合排放许可要求
Conclusion	-	DATA

Note 注释:

Temp. = Temperature/温度

deg. C = degree Celsius (°C)/摄氏度

Discharge License Criteria/排放标准: 6-9

Color [m⁻¹] (436nm; 525nm; 620nm)/色度

Test Method : With reference to ISO 7887-B
测试方法 参考 ISO 7887-B

Tested Item(s)	Result	Unit	Conclusion
I003	3.5;2.7;3.1	m ⁻¹	DATA/数据

Note 注释:

Discharge License Criteria/排放标准: N/A



Technical Report:

(6621)320-0353

November 29, 2020

Page 8 of 33

Biochemical Oxygen Demand (BOD₅)/五日生化需氧量

Test Method : Reference to HJ 505
测试方法 : 参考 HJ 505

Tested Item(s)	Result	Unit	Conclusion
I003	22.6 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤50

Ammonium Nitrogen/氨态氮

Test Method : Reference to HJ 535
测试方法 : 参考 HJ 535

Tested Item(s)	Result	Unit	Conclusion
I003	0.058 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤20

Total Phosphorus (Total-P)/总磷

Test Method : Reference to GB/T 11893
测试方法 : 参考 GB/T 11893

Tested Item(s)	Result	Unit	Conclusion
I003	0.42 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note/注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤1.5



Technical Report:

(6621)320-0353

November 29, 2020

Page 9 of 33

Adsorbable Organic Halogen (AOX)/ 可吸附有机卤化物

Test Method : Reference to HJ/T 83
测试方法 参考 HJ/T 83

Tested Item(s)	Result	Unit	Conclusion
I003	0.17 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤12

Oil and Grease/油和油脂

Test Method : Reference to HJ 637
测试方法 参考 HJ 637

Tested Item(s)	Result	Unit	Conclusion
I003	0.36	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: N/A

Phenol/苯酚

Test Method : Reference to HJ 503
测试方法 参考 HJ 503

Tested Item(s)	Result	Unit	Conclusion
I003	<0.0003	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: N/A



Technical Report:

(6621)320-0353

November 29, 2020

Page 10 of 33

Coliform/大肠菌群

Test Method : Reference to GB/T 5750.12
测试方法 参考 GB/T 5750.12

Tested Item(s)	Result	Unit	Conclusion
I003	$<1.0 \times 10^4$	Bacteria /100 mL 细菌数/100 毫升	DATA/数据

Note 注释:

bacteria/100 mL = bacteria per 100 milliliters/每 100 毫升细菌数
Discharge License Criteria/排放标准: N/A

Persistent Foam /持泡性

Test Method : Visual
测试方法 目测

Tested Item(s)	Result	Unit	Conclusion
I003	No foam 无泡沫	-	DATA/数据

ANIONS – Cyanide 阴离子-氰化物

Test Method : Reference to HJ 484
测试方法 参考 HJ 484

Tested Item(s)	Result	Unit	Conclusion
I003	<0.02	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: N/A

ANIONS – Sulfide/阴离子-硫化物

Test Method : Reference to GB/T 16489
测试方法 参考 GB/T 16489

Tested Item(s)	Result	Unit	Conclusion
I003	<0.005 Meet discharge license criteria 符合排放许可要求	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升
Discharge License Criteria/排放标准: ≤ 0.5



Technical Report:

(6621)320-0353

November 29, 2020

Page 11 of 33

ANIONS – Sulfite/阴离子-亚硫酸盐

Test Method : Reference to ISO 10304-3
测试方法 参考 ISO 10304-3

Tested Item(s)	Result	Unit	Conclusion
I003	<0.2	mg/L/ 毫克/升	DATA/数据

Note 注释:

mg/L = milligram per liter/毫克每升

Discharge License Criteria/排放标准: N/A

1B) Conventional Parameters – METALS 常规参数-重金属

Heavy Metals/重金属	I001 (mg/L)/ 毫克/升	I002 (mg/L)/ 毫克/升	I003 (mg/L)/ 毫克/升
Antimony(Sb)/锑 Discharge License Criteria/排放标准: N/A	ND	0.008	0.020
Chromium(Cr), total/总铬 Discharge License Criteria/排放标准: N/A	0.002	0.003	0.001
Cobalt(Co)/钴 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Copper(Cu)/铜 Discharge License Criteria/排放标准: N/A	ND	0.009	ND
Nickel (Ni)/镍 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Silver (Ag)/银 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Zinc(Zn)/锌 Discharge License Criteria/排放标准: N/A	0.030	0.015	0.006
Arsenic (As)/砷 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Cadmium(Cd)/镉 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Chromium VI(CrVI)/六价铬 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Lead(Pb)/铅 Discharge License Criteria/排放标准: N/A	ND	ND	ND
Mercury (Hg)/汞 Discharge License Criteria/排放标准: N/A	0.00024	0.00045	0.00043



Technical Report:

(6621)320-0353

November 29, 2020

Page 12 of 33

Others Priority Chemical Groups/其他优先化学物质

	I001	I002	I003
2A) APs and APEOs/ 烷基酚及烷基酚聚氧乙烯醚	NR	ND	ND
2B) Chlorobenzenes and Chlorotoluenes/ 氯化苯和氯甲苯	NR	ND	ND
2C) Chlorophenols/氯酚	NR	ND	ND
2D) Azo Dyes/偶氮染料	NR	ND	ND
2E) Carcinogenic Dyes/致癌染料	NR	ND	ND
2F) Disperse Dyes/分散染料	NR	ND	ND
2G) Flame Retardants/阻燃剂	NR	ND	ND
2H) Glycols/乙二醇	NR	ND	ND
2I) Halogenated Solvents/卤化溶剂	NR	ND	ND
2J) Organotin Compounds/有机锡化合物	NR	ND	ND
2K) Perfluorinated and Polyfluorinated Chemicals/全氟化合物和多氟化合物	NR	ND	ND
2L) Phthalates/邻苯二甲酸盐	NR	ND	ND
2M) Poly Aromatic Hydrocarbons/多环芳香烃	NR	ND	ND
2N) Volatile Organic Compounds/ 挥发性有机化合物	NR	ND	ND

Remark 备注：

- Test method, reporting limit and list of chemical are summarized in tables of Appendix B.
测试方法，报告限值和所列化学物质在附录 B 中
- ND = Not detected 未检出 (Please refer to reporting limit shown in Appendix B. 起报限值参考附录 B).
NR = Not required 未要求
- ppb = part(s) per billion 十亿分之一; ppm = part(s) per million 百万分之一

APPENDIX A - Photo of the Sample/ Sampling Location

样品照片/取样地照片

I001) Sampling Point

取样点

N 34°24'33"

E 117°23'24"



I001) Sampling Point Surrounding Environment

取样点周围环境

N 34°24'33"

E 117°23'24"



I001) All sampled bottles with label

全部带标签的取样瓶



I001) pH value

pH 值



I001) Sample for Phthalate Testing
邻苯测试样品



I001) Packaging
包装



I002) Sampling Point
取样点

N 34°24'41"

E 117°23'17"



I002) Sampling Point Surrounding Environment
取样点周围环境

N 34°24'41"

E 117°23'17"



I002) All sampled bottles with label
全部带标签的取样瓶



I002) pH value
pH 值



I002) Sample for Phthalate Testing
邻苯测试样品



I002) Packaging
包装



I003) Sampling Point
取样点

N 34°24'33"


E 117°23'30"



I003) Sampling Point Surrounding Environment
取样点周围环境

N 34°24'33"


E 117°23'30"



I003) All sampled bottles with label
全部带标签的取样瓶



I003) pH value
pH 值



I003) Sample for Phthalate Testing
邻苯测试样品



I003) Packaging
包装





Technical Report:

(6621)320-0353

November 29, 2020

Page 17 of 33

APPENDIX B/附录 B

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
2A. Alkylphenol (AP) and Alkylphenol Ethoxylates (APEOs): including all isomers/烷基酚及烷基酚聚氧乙烯醚包括同分异构体	Nonylphenol NP, mixed isomers /壬基苯酚及同分异构体	Various (incl. 104-40-5, 11066-49-2, 25154-52-3, 84852-15-3)	5	0.4	NP/OP: ISO 18857-2 (modified dichloromethane extraction) or ASTM D7065 (GC/MS or LC/MS(-MS))
	Octylphenol OP, mixed isomers/辛基苯酚及同分异构体	Various (incl. 140-66-9, 1806-26-4, 27193-28-8)	5	0.4	
	Octylphenol Ethoxylates (OPEO)/ 辛基酚乙 烯醚	Various (incl. 9002-93-1, 9036-19-5, 68987-90-6)	5	0.4	OPEO/NPEO: ISO18857-2 or ASTM D7065(LC/MS; GC/MS or LC/MSMS for n=1,2) APEO 1-18
	Nonylphenol Ethoxylates (NPEO)/ 壬基酚乙 烯醚	Various (inc. 9016-45-9, 26027-38-3, 37205-87-1, 68412-54-4, 127087-87-0)	5	0.4	
2B. Chlorobenzenes and Chlorotoluenes/氯化苯和氯甲苯	Chlorobenzene/氯化苯	108-90-7	0.2	0.2	USEPA 8260B,8270D. Dichloromethane extraction followed by GC/MS
	1,2-Dichlorobenzene/1,2-二氯苯	95-50-1	0.2	0.2	
	1,3-Dichlorobenzene / 1,3-二氯苯	541-73-1	0.2	0.2	
	1,4-Dichlorobenzene / 1,4-二氯苯	106-46-7	0.2	0.2	
	1,2,3-Trichlorobenzene / 1,2,3-三氯苯	87-61-6	0.2	0.2	
	1,2,4-Trichlorobenzene / 1,2,4-三氯苯	120-82-1	0.2	0.2	
	1,3,5-Trichlorobenzene / 1,3,5-三氯苯	108-70-3	0.2	0.2	
	1,2,3,4-Tetrachlorobenzene/ 1,2,3,4-四氯苯	634-66-2	0.2	0.2	
	1,2,3,5-Tetrachlorobenzene/ 1,2,3,5-四氯苯	634-90-2	0.2	0.2	
	1,2,4,5-Tetrachlorobenzene/ 1,2,4,5-四氯苯	95-94-3	0.2	0.2	
	Pentachlorobenzene/五氯苯	608-93-5	0.2	0.2	
	Hexachlorobenzene/六氯苯	1198-74-1	0.2	0.2	
	2-Chlorotoluene / 2-氯甲苯	95-49-8	0.2	0.2	
	3-Chlorotoluene / 3-氯甲苯	108-41-8	0.2	0.2	
	4-Chlorotoluene / 4-氯甲苯	106-43-4	0.2	0.2	
	2,3-Dichlorotoluene / 2,3-二氯甲苯	32768-54-0	0.2	0.2	



Technical Report:

(6621)320-0353

November 29, 2020

Page 18 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	2,4-Dichlorotoluene / 2,4-二氯甲苯	95-73-8	0.2	0.2	
	2,5-Dichlorotoluene / 2,5-二氯甲苯	19398-61-9	0.2	0.2	
	2,6-Dichlorotoluene / 2,6-二氯甲苯	118-69-4	0.2	0.2	
	3,4-Dichlorotoluene / 3,4-二氯甲苯	95-75-0	0.2	0.2	
	3,5-Dichlorotoluene / 3,5-二氯甲苯	25186-47-4	0.2	0.2	
	2,3,4-Trichlorotoluene / 2,3,4-三氯甲苯	7359-72-0	0.2	0.2	
	2,3,6-Trichlorotoluene / 2,3,6-三氯甲苯	2077-46-5	0.2	0.2	
	2,4,5-Trichlorotoluene / 2,4,5-三氯甲苯	6639-30-1	0.2	0.2	
	2,4,6-Trichlorotoluene / 2,4,6-三氯甲苯	23749-65-7	0.2	0.2	
	3,4,5-Trichlorotoluene / 3,4,5-三氯甲苯	21472-86-6	0.2	0.2	
	2,3,4,5-Tetrachlorotoluene / 2,3,4,5-四氯甲苯	76057-12-0	0.2	0.2	
	2,3,5,6-Tetrachlorotoluene / 2,3,5,6-四氯甲苯	29733-70-8	0.2	0.2	
	2,3,4,6-Tetrachlorotoluene / 2,3,4,6-四氯甲苯	875-40-1	0.2	0.2	
	Pentachlorotoluene / 五氯甲苯	877-11-2	0.2	0.2	
2C. Chlorophenols/ 氯酚	2-Chlorophenol/ 2-氯苯酚	95-57-8	0.5	0.05	USEPA 8270 D Solvent extraction, derivatisation with KOH, acetic anhydride followed by GC/MS
	3-Chlorophenol/ 3-氯苯酚	108-43-0	0.5	0.05	
	4-Chlorophenol/ 4-氯苯酚	106-48-9	0.5	0.05	
	2,3-Dichlorophenol/ 2,3-二氯苯酚	576-24-9	0.5	0.05	
	2,4-Dichlorophenol/ 2,4-二氯苯酚	120-83-2	0.5	0.05	
	2,5-Dichlorophenol/ 2,5-二氯苯酚	583-78-8	0.5	0.05	
	2,6-Dichlorophenol/ 2,6-二氯苯酚	87-65-0	0.5	0.05	
	3,4-Dichlorophenol/ 3,4-二氯苯酚	95-77-2	0.5	0.05	
	3,5-Dichlorophenol/ 3,5-二氯苯酚	591-35-5	0.5	0.05	
	2,3,4-Trichlorophenol/ 2,3,4-三氯苯酚	15950-66-0	0.5	0.05	



Technical Report:

(6621)320-0353

November 29, 2020

Page 19 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	2,3,5-Trichlorophenol/ 2,3,5-三氯苯酚	933-78-8	0.5	0.05	
	2,3,6-Trichlorophenol/ 2,3,6-三氯苯酚	933-75-5	0.5	0.05	
	2,4,5-Trichlorophenol/ 2,4,5-三氯苯酚	95-95-4	0.5	0.05	
	2,4,6-Trichlorophenol/ 2,4,6-三氯苯酚	88-06-2	0.5	0.05	
	3,4,5-Trichlorophenol/ 3,4,5-三氯苯酚	609-19-8	0.5	0.05	
	2,3,4,5-Tetrachlorophenol/ 2,3,4,5-四氯苯酚	4901-51-3	0.5	0.05	
	2,3,4,6-Tetrachlorophenol/ 2,3,4,6-四氯苯酚	58-90-2	0.5	0.05	
	2,3,5,6-Tetrachlorophenol/ 2,3,5,6-四氯苯酚	935-95-5	0.5	0.05	
	Pentachlorophenol (PCP)/ 五氯苯酚	87-86-5	0.5	0.05	
2D. Dyes - Azo (Forming Restricted Amines)/ 偶氮染料 (形成限制胺类)	4,4'-Methylene-bis-(2-chloro-aniline)/ 4,4'-亚甲基-二-(2-氯苯胺)	101-14-4	0.1	0.2	EN 14362. Reduction step with Sodiumdithionite, solvent extraction, GC/MS or LC/MS
	4,4'-methylenedianiline/ 4,4'-二氨基二苯甲烷	101-77-9	0.1	0.2	
	4,4'-Oxydianiline/ 4,4'-二氨基二苯醚	101-80-4	0.1	0.2	
	4-Chloroaniline/4-氯苯胺	106-47-8	0.1	0.2	
	3,3'-Dimethoxybenzidine/ 3,3'-二甲氧基联苯胺	119-90-4	0.1	0.2	
	3,3'-Dimethylbenzidine/ 3,3'-二甲基联苯胺	119-93-7	0.1	0.2	
	6-methoxy-m-toluidine (p-Cresidine)/ 6-甲氧基间甲苯胺	120-71-8	0.1	0.2	
	2,4,5-Trimethylaniline/ 2,4,5-三甲基苯胺	137-17-7	0.1	0.2	
	4,4'-Thiodianiline	139-65-1	0.1	0.2	
	4-Aminoazobenzene/ 4-氨基偶氮苯	60-09-3	0.1	0.2	
	4-Methoxy-m-phenylenediamine/ 4-甲氧基-间苯二胺	615-05-4	0.1	0.2	
	4,4'-Methylene-di-o-toluidine/4,4'-二甲基-邻甲苯胺 /	838-88-0	0.1	0.2	
	2,6-Xylidine/ 2,6-二甲基苯胺	87-62-7	0.1	0.2	
	o-Anisidine/邻氨基苯甲醚	90-04-0	0.1	0.2	
	2-Naphthylamine/2-萘胺	91-59-8	0.1	0.2	



Technical Report:

(6621)320-0353

November 29, 2020

Page 20 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	3,3'-Dichlorobenzidine/ 3,3'-二氯联苯胺	91-94-1	0.1	0.2	
	4-Aminodiphenyl/ 4-氨基联苯	92-67-1	0.1	0.2	
	Benzidine/联苯胺	92-87-5	0.1	0.2	
	o-Toluidine/邻甲苯胺	95-53-4	0.1	0.2	
	2,4-Xylidine/2,4-二甲基苯胺	95-68-1	0.1	0.2	
	4-Chloro-o-toluidine/4-氯邻甲苯胺	95-69-2	0.1	0.2	
	4-Methyl-m-phenylenediamine/ 4-甲基间苯二胺	95-80-7	0.1	0.2	
	o-Aminoazotoluene/邻氨基偶氮甲苯	97-56-3	0.1	0.2	
	5-nitro-o-toluidine/5-硝基邻甲苯胺	99-55-8	0.1	0.2	
2E. Dyes-Carcinogenic or Equivalent Concern/ 致癌染料或涉及的同类	C.I. Direct Black 38/ C.I.直接黑 38	1937-37-7	500	10	Liquid Extraction LC/MS
	C.I. Direct Blue 6/ C.I.直接蓝 6	2602-46-2	500	10	
	C.I. Acid Red 26/ C.I.酸性红 26	3761-53-3	500	10	
	C.I. Basic Red 9/ C.I.碱性红 9	569-61-9	500	10	
	C.I. Direct Red 28/ C.I.直接红 28	573-58-0	500	10	
	C.I. Basic Violet 14/ C.I.碱性紫 14	632-99-5	500	10	
	C.I. Disperse Blue 1 / C.I. 分散蓝 1	2475-45-8	500	10	
	C.I. Disperse Blue 3 / C.I. 分散蓝 3	2475-46-9	500	10	
	C.I. Basic Blue 26 (with Michler's Ketone > 0.1%) / C.I. 碱性蓝 26 (米氏酮 > 0.1%)	2580-56-5	500	10	
	C.I. Basic Green 4 (malachite green chloride)/ C.I. 碱性绿 4(孔雀石绿氯化物)	569-64-2	500	10	
	C.I. Basic Green 4 (malachite green oxalate)/ C.I. 碱性绿 4(孔雀石绿草	2437-29-8	500	10	



Technical Report:

(6621)320-0353

November 29, 2020

Page 21 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	酸盐)				
	C.I. Basic Green 4(malachite green)/ C.I. 碱性绿 4(孔雀石绿)	10309-95-2	500	10	
	Disperse Orange 11/分散橙 11	82-28-0	500	10	
2F. Dyes-disperse (sensitizing)/ 分散染料 (致敏)	Disperse Yellow 1 / 分散黄 1	119-15-3	50	2	Liquid Extraction LC/MS
	Disperse Blue 102 / 分散蓝 102	12222-97-8	50	2	
	Disperse Blue 106 / 分散蓝 106	12223-01-7	50	2	
	Disperse Yellow 39 / 分散黄 39	12236-29-2	50	2	
	Disperse Orange 37/59/76 / 分散橙 37/59/76	13301-61-6	50	2	
	Disperse Brown 1 / 分散棕 1	23355-64-8	50	2	
	Disperse Orange 1/ 分散橙 1	2581-69-3	50	2	
	Disperse Yellow 3/ 分散黄 3	2832-40-8	50	2	
	Disperse Red 11/分散红 11	2872-48-2	50	2	
	Disperse Red 1/分散红 1	2872-52-8	50	2	
	Disperse Red 17 / 分散红 17	3179-89-3	50	2	
	Disperse Blue 7 /分散蓝 7	3179-90-6	50	2	
	Disperse Blue 26 / 分散蓝 26	3860-63-7	50	2	
	Disperse Yellow 49 / 分散黄 49	54824-37-2	50	2	
	Disperse Blue 35 / 分散蓝 35	12222-75-2	50	2	
	Disperse Blue 124 / 分散蓝 124	61951-51-7	50	2	
	Disperse Yellow 9 / 分散黄 9	6373-73-5	50	2	
	Disperse Orange 3 / 分散橙 3	730-40-5	50	2	
2G. Flame Retardants/阻燃剂	Tris(2-chloroethyl) phosphate (TCEP)/ 三(2-氯乙基)磷酸酯	115-96-8	5	1	ISO 22032, USEPA527 and USEPA8321B. Dichloromethane extraction GC/MS or LC/MS(-MS)
	Decabromodiphenyl ether (DecaBDE)/ 十溴联苯醚	1163-19-5	5	1	
	Tris(2,3-dibromopropyl) phosphate (TRIS/TDBPP)/ 三(2, 3-二溴丙基)磷	126-72-7	5	1	



Technical Report:

(6621)320-0353

November 29, 2020

Page 22 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	酸酯				
	Pentabromodiphenyl ether (PentaBDE)/ 五溴联苯醚 (PentaBDE)	32534-81-9	5	1	
	Octabromodiphenyl ether (OctaBDE)/ 八溴联苯醚	32536-52-0	5	1	
	Bis(2,3-dibromopropyl) phosphate (BIS/BDBPP)/ 二(2,3-二溴丙基)磷酸酯	5412-25-9	5	1	
	Tris(aziridinyl)-phosphineoxide (TEPA)/ 三-(氮环丙基)-膦化氧	545-55-1	5	1	
	Polybromobiphenyls (PBBs)/多溴联苯	59536-65-1	5	1	
	Tetrabromobisphenol A (TBBPA)/ 四溴双酚 A	79-94-7	5	1	
	Hexabromocyclododecane (HBCDD)/六溴环十二烷	3194-55-6	5	1	
	2,2-Bis(bromomethyl)-1,3-propanediol (BBMP)/ 2,2-二(溴甲基)-1,3-丙二醇	3296-90-0	5	1	
	Tris(1,3-dichloroisopropyl) phosphate (TDCP)/ 三(1,3-二氯异丙基)磷酸酯	13674-87-8	5	1	
	Short chain chlorinated paraffins (SCCPs) (C10-C13)/短链氯化石蜡	85535-84-8	5	1	
2H. Glycols/乙二醇	Bis(2-methoxyethyl)-ether / 二甘醇二甲醚	111-96-6	50	10	US EPA 8270 Liquid Extraction LC/MS
	2-ethoxyethanol / 乙二醇单乙醚	110-80-5	50	10	
	2-ethoxyethyl acetate / 乙二醇乙醚醋酸酯	111-15-9	50	10	
	Ethylene glycol dimethyl ether/ 乙二醇二甲醚	110-71-4	50	10	
	2-methoxyethanol / 乙二醇甲醚	109-86-4	50	10	
	2-methoxyethylacetate / 乙二醇甲醚乙酸酯	110-49-6	50	10	
	2-methoxypropylacetate/ 2-甲基丙醇乙酸酯	70657-70-4	50	10	
	Triethylene glycol dimethyl ether/ 三乙二醇二甲醚	112-49-2	50	10	
2I. Halogenated Solvents/卤化溶剂	1,2-Dichloroethane/ 1,2-二氯乙烷	107-06-2	1	2	USEPA 8260B Headspace GC/MS or

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	Methylene Chloride/二氯甲烷	75-09-2	1	2	Purgeand-Trap-GC/MS
	Trichloroethylene/三氯乙烯	79-01-6	1	2	
	Tetrachloroethylene/四氯乙烯	127-18-4	1	2	
2J. Organotin Compounds/ 有机锡化合物	Mono-, di- and tri-methyltin derivatives/ 一,二,三-甲基锡衍生物	Multiple	0.01	0.2	ISO 17353 Derivatisation with NaB(C ₂ H ₅) GC/MS
	Mono-, di- and tri-butyltin derivatives/ 一,二,三-丁基锡衍生物	Multiple	0.01	0.2	
	Mono-, di- and tri-phenyltin derivatives/ 一,二,三-苯基锡衍生物	Multiple	0.01	0.2	
	Mono-, di- and tri-octyltin derivatives/ 一,二,三-辛基锡衍生物	Multiple	0.01	0.2	
	Monomethyltin /一甲基锡	Multiple	0.01	0.2	
	Dimethyltin /二甲基锡	Multiple	0.01	0.2	
	Trimethyltin /三甲基锡	Multiple	0.01	0.2	
	Monobutyltin /一丁基锡	Multiple	0.01	0.2	
	Dibutyltin/二丁基锡	Multiple	0.01	0.2	
	Tributyltin /三丁基锡	Multiple	0.01	0.2	
	Monophenyltin /一苯基锡	Multiple	0.01	0.2	
	Diphenyltin /二苯基锡	Multiple	0.01	0.2	
	Triphenyltin /三苯基锡	Multiple	0.01	0.2	
	Monooctyltin /一辛基锡	Multiple	0.01	0.2	
	Diocetyltn/二辛基锡	Multiple	0.01	0.2	
	Tetrabutyltin /四丁基锡	Multiple	0.01	0.2	
2K. Perfluorinated and Polyfluorinated Chemicals (PFCs)/ 全氟化合物和多氟化合物	Perfluorooctanesulfonic acid (PFOS)/ 全氟辛烷磺酸	355-46-4 ,432-50-7	0.01	0.10	DIN 38407-42 (modified) Ionic PFC: Concentration or direct injection, LC/MS(-MS); Non-ionic PFC (FTOH): derivatisation with acetic anhydride, followed by GC/MS
	Perfluoro-n-octanoic acid (PFOA)/ 全氟辛酸	335-67-1/ 335-95-5	0.01	0.10	
	Perfluorobutanesulfonic acid (PFBS)/ 全氟丁基磺酸	29420-49-3, 29420-43-3	0.01	0.10	
	Perfluoro-n-hexanoic acid (PFHxA)/ 全氟己酸	307-24-4	0.01	0.10	
	8:2 FTOH/8:2-全氟辛基乙醇	678-39-7	1	1	
	6:2 FTOH/6:2-全氟乙醇	647-42-7	1	1	
2L. Phthalates (including all other esters of phthalic acid)/ 苯二甲酸盐 (包括	Di-2-ethylhexyl phthalate (DEHP)/ 邻苯二甲酸二 (2-乙基己基酯)	117-81-7	10	2	US EPA 8270D, ISO 18856 Dichloromethane extraction GC/MS
	Dimethoxyethyl phthalate	117-82-8	10	2	

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
其他邻苯二甲酸酯类)	(DMEP)/邻苯二甲酸二甲氧基乙酯				
	Di-n-octyl phthalate (DNOP)/邻苯二甲酸二辛酯	117-84-0	10	2	
	Di-iso-decyl phthalate (DIDP)/邻苯二甲酸二异癸酯	26761-40-0	10	2	
	Di-iso-nonyl phthalate (DINP)/邻苯二甲酸二异壬酯	28553-12-0	10	2	
	Di-n-hexyl phthalate (DnHP)/邻苯二甲酸二己酯	84-75-3	10	2	
	Dibutyl phthalate (DBP)/邻苯二甲酸二丁酯	84-74-2	10	2	
	Butyl benzyl phthalate (BBP)/邻苯二甲酸丁苄酯	85-68-7	10	2	
	Dinonyl phthalate (DNP)/邻苯二甲酸二壬酯	84-76-4	10	2	
	Diethyl phthalate (DEP)/邻苯二甲酸二乙酯	84-66-2	10	2	
	Di-n-propyl phthalate (DPRP)/邻苯二甲酸二丙酯	131-16-8	10	2	
	Di-iso-butyl phthalate (DIBP)/邻苯二甲酸二异丁酯	84-69-5	10	2	
	Di-cyclohexyl phthalate (DCHP)/邻苯二甲酸二环己酯	84-61-7	10	2	
	Di-iso-octyl phthalate (DIOP)/邻苯二甲酸二异辛酯	27554-26-3	10	2	
	1,2-benzenedicarboxylic acid, di-C7-11-branched and linearalkyl esters (DHNUP)/邻苯二甲酸-二(C7-C11 支链与直链)	68515-42-4	10	2	
	1,2-benzenedicarboxylic acid, di-C6-8-branched alkyl esters, C7-rich (DIHP)/邻苯二甲酸二支链烷基酯	71888-89-6	10	2	
2M. Poly Aromatic Hydrocarbons (PaHs)/多环芳香烃	Benzo[a]pyrene (BaP) /苯并[a]芘	50-32-8	1	0.2	DIN 38407-39 Solvent extraction GC/MS
	Anthracene /蒽	120-12-7	1	0.2	
	Pyrene /芘	129-00-0	1	0.2	



Technical Report:

(6621)320-0353

November 29, 2020

Page 25 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	Benzo[ghi]perylene / 苯并[g,h,i]芘	191-24-2	1	0.2	
	Benzo[e]pyrene / 苯并[e]芘	192-97-2	1	0.2	
	Indeno[1,2,3-cd]pyrene / 茚并[1,2,3-cd]芘	193-39-5	1	0.2	
	Benzo[j]fluoranthene / 苯并[j]荧蒽	205-82-3	1	0.2	
	Benzo[b]fluoranthene / 苯并[b]荧蒽	205-99-2	1	0.2	
	Fluoranthene / 荧蒽	206-44-0	1	0.2	
	Benzo[k]fluoranthene / 并[k]荧蒽	207-08-9	1	0.2	
	Acenaphthylene / 芴	208-96-8	1	0.2	
	Chrysene / 屈	218-01-9	1	0.2	
	Dibenz[a,h]anthracene / 二苯并[a,h]蒽	53-70-3	1	0.2	
	Benzo[a]anthracene / 苯并[a]蒽	56-55-3	1	0.2	
	Acenaphthene / 二氢芴	83-32-9	1	0.2	
	Phenanthrene / 菲	85-01-8	1	0.2	
	Fluorene / 芴	86-73-7	1	0.2	
	Naphthalene / 萘	91-20-3	1	0.2	
2N. Volatile Organic Compound (VOCs)/挥发性有机化合物	Benzene / 苯	71-43-2	1	2	ISO 11423-1 Headspace- or Purge-and-Trap-GC/MS
	Xylene / 二甲苯	1330-20-7	1	2	
	o-cresol / 邻甲苯酚	95-48-7	1	2	
	p-cresol / 对甲苯酚	106-44-5	1	2	
	m-cresol / 间甲苯酚	108-39-4	1	2	
1A. Conventional Parameters /常规参数	Temperature/温度	—	N/A	N/A	Apply the standard methods that best apply to the region (ISO, EU, US, China), please refer to ZDHC Wastewater Guidelines for more details on the testing method and the levels (Exceeded Foundational Limit, Foundational, Progressive, and Aspirational).
	TSS/总悬浮固体	—	N/A	N/A	
	COD/化学需氧量	—	N/A	N/A	
	Total-N/总氮	—	N/A	N/A	
	pH/酸碱值	—	N/A	N/A	
	Color [m ⁻¹] (436nm; 525nm; 620nm)/色度	—	N/A	N/A	
	BOD ₅ /五日生化需氧量	—	N/A	N/A	
	Ammonium-N/氨态氮	—	N/A	N/A	
	Total-P/总磷	—	N/A	N/A	
	AOX/可吸附有机卤化物	—	N/A	N/A	
	Oil and Grease/油和油脂	—	N/A	N/A	
	Phenol/苯酚	—	N/A	N/A	
	Coliform(bacteria/100ml)/大肠菌群	—	N/A	N/A	
	Persistent Foam/泡沫持久性	—	Not visible	Not visible	
	ANIONS/阴离子	—			



Technical Report:

(6621)320-0353

November 29, 2020

Page 26 of 33

Group /组别	Substance (Testing parameter)/物质(测试参数)	CAS No./化学物质登记号	Report Limit /报告限值		Name of the testing method/测试方法名称
			Wastewater /废水 (ug/L)/(ppb)	Sludge /淤泥 (mg/kg)/(ppm)	
	Cyanide(CN-)/氰化物	Various (incl. 57-12-5)	0.02	1	
	Sulfide/硫化物	—	N/A	N/A	
	Sulfite/亚硫酸盐	—	N/A	N/A	
Group	Substance (Testing parameter)	CAS No.	Report Limit		Name of the testing method
			Wastewater (mg/L) / (ppm)	Wastewater (mg/kg) / (ppm)	
1B. Conventional Parameters – METALS/常规参数-重金属	Antimony(Sb)/锑	7440-36-0	0.001	N/A	Various Acid Digestion with ICP analysis
	Chromium(Cr), total/总铬	7440-47-3	0.001	N/A	
	Cobalt(Co)/钴	7440-48-4	0.001	N/A	
	Copper(Cu)/铜	7440-50-8	0.001	N/A	please refer to ZDHC Wastewater Guidelines for more details on the testing method and the levels (Foundational, Progressive, and Aspirational).
	Nickel(Ni)/镍	7440-02-0	0.001	N/A	
	Silver(Ag)/银	7440-22-4	0.001	N/A	
	Zinc(Zn)/锌	7440-66-6	0.001	N/A	
	Arsenic(As)/砷	7440-38-2	0.001	2	
	Cadmium(Cd)/镉	7440-43-9	0.0001	2	
	Chromium VI(CrVI)/六价铬	18540-29-9	0.001	2	Cr(VI): Various Solvent extraction and derivatisation followed by UV analysis
	Lead(Pb)/铅	7439-92-1	0.001	2	
	Mercury(Hg)/汞	7439-97-6	0.00005	0.2	

Note / Key :

注释/要点:

ppb = part(s) per billion /ppb = 十亿分之一; ppm = part(s) per million/百万分之一

U. S. EPA = United States Environmental Protection Agency/美国环境保护署

APHA = American Public Health Association/美国公共卫生协会

N/A = Not Applicable 不适用



Technical Report:

(6621)320-0353

November 29, 2020

Page 27 of 33

APPENDIX C – Onsite Field Data Record Sheet

附录 C-现场采样记录表

FIELD DATA RECORD ON ZERO DISCHARGE SAMPLE (COMPOSITE / INDIVIDUAL SAMPLING)		CPSD-AN-00613-DATA 04	
		Issue Date:	
		Version No.: 11	
		Business Line: Analytical	
General Data			
Laboratory Sample Number:	66213200353		
Client Name:	江苏新鹏成集团环保科技有限公司 / 江苏省徐州市贾汪区青山泉镇		
Field Contact Person:	陈平 Phone No: 18965209326		
Project (Facility Name and Address):	污水取样口		
Sampling Location / Description:	Zero discharge with sampling plan		
Sample Identification:	Composite Sample / Grab sample (Please delete as appropriate)		
Sample Type:	Grab sample		
Name of Sampler:	2021.11.16		
Discharge mode:	Direct discharge to environment (Specify destination: River, Sea, Stream...) OR indirect discharge to sewage treatment plant		
Date of collection:	2021.11.16		
Factory Type:	Dyeing / Printing / Washing / Finishing / Others (please specify):		
*Note: It would be selected more than one			
Field Data for Wastewater			
Arrival Time:	8:50	Departure Time:	11:30
Field Parameters:	pH: 8.23	Temp: 17.2 °C	Color: 1530
Control No. of field equipment:	CA-002M1	CA-002M1	
Factory with effluent treatment plant:	No		
Sample matrix:	Incoming water (if required) Wastewater before treatment Wastewater after treatment - water at discharge point		
Sampler container number:	A1		
Recording time:	ID: A1		
pH:	8.23		
Temp (°C):	17.2		
Color:	1530		
Flow rate (volume/time):			
Volume collected, mL:	482		
Total volume collected:	482	Remark: Total volume collected must be greater than total of sample size required	
Analysis Required and Preservation Method			
Tests (ZDHC MRSI Parameters)	Test required (v)	Total of sample size	Preservation method
Combined test or Individual test (Remark 4)	1. Phthalate 2. Chlorobenzenes, Chlorotoluene & PAH 3. SCCPs 4. APS	1000 mL total or 1000 mL each	Amber Glass washed with nitric acid, rinsed thoroughly with distilled water and dried before use
5. APEOs	✓	100 mL	Without adding acid Store sample at 6°C
6. Chlorophenols & Cresols	✓	100 mL	
7. Flame retardant	✓	500 mL	
8. Dyes	✓	10 mL	
9. Glycol	✓	50 mL	
10. Pesticides		1000 mL	
11. Nitrosamine		10 mL	
12. Banned Azodyes	✓	2000 mL	
13. Free primary aromatic amines		500 mL	
14. Organotin Compounds	✓	500 mL	Acidify to pH 2 with HCl and store sample at 6°C
15. VOC & Halogenated Solvents (Remark 6)	✓	10 mL	Acidify to pH 2 with HCl and store sample at 6°C
16. PFCS	✓	2 mL	Without adding acid Store sample at 6°C



Technical Report:

(6621)320-0353

November 29, 2020

Page 28 of 33

Tests (Conventional Parameters)	Test required (Y)	Total of sample size	Type of container	Preservation method
Combined test or Individual test (Remark 4)	17. Total suspended solids (TSS) 18. Total dissolved solids (TDS)	2000 mL total or 2000 mL each	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
19. 5-day Biochemical Oxygen Demand (BOD5)		1000 mL		
20. Heavy Metals except Cr(VI) & Total-P (Remark 6)	✓	9 mL	PE, washed with nitric acid, pre-add 6.5 mL of 2M HNO ₃	Acidify to pH 2 with HNO ₃ and store at 6°C
21. Cr(VI)	✓	95 mL	Amber Glass, washed with pesticide grade acetone	Filter by 0.45µm filter in field, fill to full container without air gap, adjust pH to 9.0-9.5 by adding ammonium buffer. Store sample at 6°C
22. Cyanide	✓	500 mL		Adjust pH 12 with 50% NaOH, add 0.05 mL of 10% Na ₂ S ₂ O ₅ and store sample at 6°C
23. Chemical oxygen demand (COD)		150 mL	Amber Glass washed with nitric acid, Pre-add 6.5 mL of 2M H ₂ SO ₄	Acidify to pH 2 with H ₂ SO ₄ , Store sample at 6°C
24. Phenols		500 mL		Fill to full container without air gap, acidify to pH 2 with H ₂ SO ₄ and store sample at 6°C
25. Formaldehyde		25 mL		
26. Sulfide (Remark 5)		50 mL	PE, washed with pesticide grade Acetone	Fill to full container without air gap, add 2 drops of 2M zinc acetate, adjust pH to 9 with 6M NaOH. Store sample at 6°C
27. Adsorbable organically bound halogens (AOX)		100 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M HNO ₃	Add 0.05 mL of 10% Na ₂ S ₂ O ₅ , acidify to pH 2 with H ₂ SO ₄ , Store sample at 6°C
28. Total Coliform (Remark 6)		125 mL	PE, clean, sterile, non-reactive	
29. Persistent foam		N.A.	Foam higher than 45 cm (visual estimation): Yes / No	
30. Sulfite		100 mL	Amber Glass, washed with pesticide grade acetone	Add 1 mL of 2.5% EDTA, 0.5g zinc acetate. Store sample at 6°C
31. Total-N		100 mL	Amber Glass with wide-mouth PTFE lid washed with nitric acid, Pre-add 6.5 mL of 2M H ₂ SO ₄	Acidify to pH 2 with H ₂ SO ₄ , Store sample at 6°C
32. Ammonium-N		500 mL		
33. Oil and Grease		1000 mL	Amber Glass washed with nitric acid, Pre-add 6.5 mL of 2M H ₂ SO ₄	
34. Total Hydrocarbon		1000 mL		
35. Luminescence Toxicity		1000 mL		
36. Sulfate		100 mL	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
37. Chloride		100 mL		
38. Others:				

*Remarks:

- Individual sampling can be performed upon request
- The minimum sampling time for 2016 ZDHC guideline is 6 hours with no more than one hour between discrete samples. Sampling time could be adjusted upon request.
- Scope of ZDHC guideline: Parameter 1, 2, 4-9, 12, 14-17, 19-24, 26-33
Scope of synthetic leather industry: Parameter 1, 2, 4-9, 12, 14-17, 19-33
Scope of MMCF: Parameter 4, 5, 17, 19-24, 26, 27, 31-37
Free primary aromatic amine, pesticides, nitroamine and TDS are not in the scope of ZDHC Guideline, they are tested upon request.
- Refer to CPD-AN-00019-STIPR1, locations with those CPD test capability inside TCD matrix can perform the combined test.
- Refer to CPD-AN-00070-MTHD for additional pretreatment of sulfide if only dissolved sulfide is required to be tested
- Refer to CPD-AN-00613-MTHD for preparation of field blank for specific parameters.

Recorded by:

Full name: 李菊明

Date: 2021.11.16

Comment from factory:

取水取样口: N 34°26'33" E 117°23'24"

Acknowledgement by factory:

I hereby confirmed that Bureau Veritas has completed the stated sampling activity at captioned date, time and location. All sample(s) is/are collected in designated container(s) and without any observation in leakage. Sample(s) collected by Bureau Veritas is/are stored in portable freezer / fridge that is maintained in 1-6°C

Signature of Factory Representative:

Full Name: 李菊明

Date: 2021.11.16



Technical Report:

(6621)320-0353

November 29, 2020

Page 29 of 33

FIELD DATA RECORD ON ZERO DISCHARGE SAMPLE
(COMPOSITE / INDIVIDUAL SAMPLING)

CPSD-AN-00613-DATA 04
Issue Date: _____
Version No.: 11
Business Line: Analytical

General Data

Laboratory Sample Number: 66213200353

Client Name: 江苏彭浦集团东桥有限公司

Field Contact Person: 王东平 Phone No: 18905209326

Project (Facility Name and Address): 江苏省徐州市贾汪区青山泉镇

Sampling Location / Description: 外排口

Sample Identification: 外排口

Sample Type: Composite Sample / Grab sample (Please delete as appropriate)

Name of Sampler: 王东平

Discharge mode: 2021.11.16

Date of collection: 2021.11.16

Factory Type: Dyeing / Printing / Washing / Finishing / Others (please specify):

*Note: It would be selected more than one

Field Data for Wastewater

Arrival Time: 8:50 Departure Time: 15:30

Field Parameters: pH: 8.50 Temp: 15.30 °C Color: 15.30 Flow rate: (volume/min)

Control No. of field equipment: CA-002M1 CA-002M1

Factory with effluent treatment plant: No

Sample matrix: Wastewater before treatment

Wastewater after treatment - water at discharge point

Sampler container number: A2 A2 A2 A2 A2 A2 A2 A2

Recording time: ID Time 9:05 10:05 11:05 12:05 13:05 14:05 15:05

pH: 8.35 8.94 8.62 8.75 8.41 8.39 8.31

Temp (°C): 39.6 39.7 39.8 39.9 37.5 38.1 39.2

Color: 淡紫色 淡紫色 淡紫色 淡紫色 淡绿色 淡绿色 淡绿色

Flow rate (volume/time): 0.92L 0.92L 0.92L 0.92L 0.92L 0.92L 1.27L

Volume collected, mL: 0.92L 0.92L 0.92L 0.92L 0.92L 0.92L 1.27L

Total volume collected: 6.82L Remark: Total volume collected must be greater than total of sample size required

Analysis Required and Preservation Method

Tests (ZDHC MRLS Parameters)	Test required (Y)	Total of sample size	Type of container	Preservation method
1. Phthalate	✓	1000 mL total or 1000 mL each	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
2. Chlorobenzenes, Chlorotoluene & PAH	✓			
3. SCCPs	✓			
4. APS	✓			
5. APEOs	✓	100 mL		
6. Chlorophenols & Cresols	✓	100 mL		
7. Flame retardant	✓	500 mL		
8. Dyes	✓	10 mL		
9. Glycol	✓	50 mL		
10. *Pesticides	✓	1000 mL		
11. *Nitrosamine	✓	10 mL		
12. Banned Azodyes	✓	2000 mL		
13. *Free primary aromatic amines	✓	500 mL		
14. Organotin Compounds	✓	500 mL	Amber Glass, washed with nitric acid, Pre-add 6.5 mL of 2M HCl	Acidify to pH 2 with HCl and store sample at 6°C
15. VOC & Halogenated Solvents (Remark 6)	✓	10 mL		Fill to full container without air gap; acidify to pH 2 with HCl and store sample at 6°C
16. PFCs	✓	2 mL	PE, washed with pesticide grade Acetone	Without adding acid Store sample at 6°C

Tests (Conventional Parameters)	Test required (Y)	Total of sample size	Type of container	Preservation method
Combined test or Individual test (Remark 4)	17. Total suspended solids (TSS) 18. Total dissolved solids (TDS)	2000 mL total or 2000 mL each	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
19. 5-day Biochemical Oxygen Demand (BOD5)		1000 mL	PE, washed with nitric acid, pre-add 6.5 mL of 2M HNO ₃	Acidify to pH 2 with HNO ₃ and store at 6°C
20. Heavy Metals except Cr(VI) & Total-P (Remark 6)	✓	9 mL	PE, washed with nitric acid, pre-add 6.5 mL of 2M HNO ₃	Filter by 0.45µm filter in field, fill to full container without air gap; adjust pH to 9.0-9.5 by adding ammonium buffer. Store sample at 6°C
21. Cr(VI)	✓	95 mL	Amber Glass, washed with pesticide grade acetone	Adjust pH 12 with 50% NaOH; add 0.05 mL of 10% Na ₂ S ₂ O ₄ and store sample at 6°C
22. Cyanide	✓	500 mL	Amber Glass, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	Acidify to pH 2 with H ₂ SO ₄ ; Store sample at 6°C
23. Chemical oxygen demand (COD)		150 mL	Amber Glass, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	Fill to full container without air gap; acidify to pH 2 with H ₂ SO ₄ and store sample at 6°C
24. Phenols		500 mL	PE, washed with pesticide grade Acetone	Fill to full container without air gap; add 2 drops of 2M zinc acetate, adjust pH to 9 with 5M NaOH. Store sample at 6°C
25. Formaldehyde		25 mL	PE, washed with pesticide grade Acetone	Add 0.05 mL of 10% Na ₂ S ₂ O ₄ , acidify to pH 2 with H ₂ SO ₄ . Store sample at 6°C
26. Sulfide (Remark 5)		50 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M HNO ₃	
27. Adsorbable organically bound halogens (AOX)		100 mL	PE, clean, sterile, non-reactive	
28. Total Coliform (Remark 6)		125 mL	Foam higher than 45 cm (visual estimation): Yes / No	
29. Persistent foam		N.A.	Amber Glass, washed with pesticide grade acetone	Add 1mL of 2.5% EDTA, 0.5g zinc acetate. Store sample at 6°C
30. Sulfite		100 mL	Amber Glass with wide-mouth PTFE lid, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	Acidify to pH 2 with H ₂ SO ₄ . Store sample at 6°C
31. Total-N		100 mL	Amber Glass, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	
32. Ammonium-N		500 mL	Amber Glass, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	
33. Oil and Grease		1000 mL	Amber Glass, washed with nitric acid; Pre-add 6.5 mL of 2M H ₂ SO ₄	
34. Total Hydrocarbon		1000 mL	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
35. Luminescent Bacteria Toxicity		1000 mL		
36. Sulfate		100 mL		
37. Chloride		100 mL		
38. Others				

Observation Remark:

*Remarks:

- Individual sampling can be performed upon request.
- The minimum sampling time for 2016 ZDHC guideline is 6 hours with no more than one hour between discrete samples. Sampling time could be adjusted upon request.
- Scope of ZDHC guideline: Parameter 1, 2, 4-9, 12, 14-17, 19-24, 26-33
Scope of synthetic leather industry: Parameter 1, 2, 4-9, 12, 14-17, 19-33
Scope of MMCF: Parameter 4, 5, 17, 19-24, 26, 27, 31-37
Free primary aromatic amine, pesticides, nitrosamine and TDS are not in the scope of ZDHC Guideline, they are tested upon request.
- Refer to CPSPD-AN-G00019-STIP01, locations with those CPSPD test capability inside TCD matrix can perform the combined test.
- Refer to CPSPD-AN-000570-MTHD for additional pretreatment of sulfide if only dissolved sulfide is required to be tested.
- Refer to CPSPD-AN-00613-MTHD for preparation of field blank for specific parameters.

Recorded by:

Full Name: 李荣明

Date:

2021.11.16

Comment from factory:

处理前取样口 N34°24'41" E117°23'17"

Acknowledgement by factory:

I hereby confirmed that Bureau Veritas has completed the stated sampling activity at captioned date, time and location. All sample(s) is/are collected in designated container(s) and without any observation in leakage. Sample(s) collected by Bureau Veritas is/are stored in portable freezer / fridge that is maintained in 1-6°C.

Signature of Factory Representative:

Full Name:

李荣明

Date:

2021.11.16



Technical Report:

(6621)320-0353

November 29, 2020

Page 31 of 33

FIELD DATA RECORD ON ZERO DISCHARGE SAMPLE (COMPOSITE / INDIVIDUAL SAMPLING)		CPSD-AN-00613-DATA 04	
		Issue Date:	
		Version No.: 11	
		Business Line: Analytical	

General Data	
Laboratory Sample Number:	66213200353
Client Name:	
Field Contact Person:	张平
Project (Facility Name and Address):	江苏新城集团建设有限公司 / 江苏省徐州市贾汪区青山泉镇
Sampling Location / Description:	外排口 取样口
Sample Identification:	Zero discharge with sampling plan
Sample Type:	Composite Sample / Grab sample (Please delete as appropriate)
Name of Sampler:	王黎明
Discharge mode:	Direct discharge to environment (Specify destination: River, Sea, Stream...) OR Indirect discharge to sewage treatment plant
Date of collection:	2021.11.16
Factory Type:	Dyeing / Printing / Washing / Finishing / Others (please specify):
*Note: It would be selected more than one	

Field Data for Wastewater	
Arrival Time:	8:50
Departure Time:	15:30
Field Parameters:	pH: Temp: °C Color: Flow rate: (volume/min)
Control No. of field equipment:	CA-002M1 CA-002M1
Factory with effluent treatment plant:	No
Sample matrix:	Incoming water (if required) Wastewater before treatment Wastewater after treatment - water at discharge point
Sampler container number:	A3 A3 A3 A3 A3 A3 A3 A3
Recording time:	ID Time
pH:	8.15 10.15 11.15 12.15 13.15 14.15 15.15
Temp (°C):	8.34 8.30 8.37 8.31 8.34 8.42 8.36
Color:	19.8 19.9 19.9 20.1 21.5 21.5 21.6
Flow rate (volume/time):	浅黄 浅黄 浅黄 浅黄 浅黄 浅黄 浅黄
Volume collected, mL:	15L 15L 15L 15L 15L 15L 250L
Total volume collected:	104L Remark: Total volume collected must be greater than total of sample size required

Analysis Required and Preservation Method					
Tests (ZDHC MRSL Parameters)	Test required (v)	Total of sample size	Type of container	Preservation method	
Combined test or Individual test (Remark 4)	1. Phthalate	✓	1000 mL total or 1000 mL each	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
	2. Chlorobenzenes, Chlorotoluene & PAH	✓			
	3. SCCPs	✓			
	4. APS	✓			
5. APEOs	✓	100 mL	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C	
6. Chlorophenols & Cresols	✓	100 mL			
7. Flame retardant	✓	500 mL			
8. Dyes	✓	10 mL			
9. Glycol	✓	50 mL			
10. *Pesticides		1000 mL			
11. *Nitrosamine		10 mL			
12. Banned Azodyes	✓	2000 mL			
13. *Free primary aromatic amines		500 mL			
14. Organotin Compounds	✓	500 mL			Amber Glass, washed with nitric acid, Pre-add 6.5 mL of 3M HCl
15. VOC & Halogenated Solvents (Remark 6)	✓	10 mL	Fit to full container without air gap; acidify to pH 2 with HCl and store sample at 6°C		
16. PFCA	✓	2 mL		Without adding acid Store sample at 6°C	

CPSD-AN-00613-DATA 04-FIELD DATA RECORD FOR ZERO DISCHARGE SAMPLE INDIVIDUAL SAMPLING-V11.xls

Page 1 of 3



Technical Report:

(6621)320-0353

November 29, 2020

Page 32 of 33

Tests (Conventional Parameters)	Test required (V)	Total of sample size	Type of container	Preservation method
Combined test or Individual test (Remark 4)	17. Total suspended solids (TSS) 18. Total dissolved solids (TDS)	2000 mL total or 2000 mL each	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
19. 5-day Biochemical Oxygen Demand (BOD ₅)	✓	1000 mL	PE, washed with nitric acid, pre-add 6.5mL of 2M HNO ₃	Acidify to pH 2 with HNO ₃ and store at 6°C
20. Heavy Metals except Cr(VI) & Total-P (Remark 6)	✓	9 mL	PE, washed with nitric acid, pre-add 6.5mL of 2M HNO ₃	Filter by 0.45µm filter in field, fill to full container without air gap; adjust pH to 9.0-9.5 by adding ammonium buffer. Store sample at 6°C
21. Cr(VI)	✓	95 mL	Amber Glass, washed with pesticide grade acetone	Adjust pH 12 with 50% NaOH, add 0.05 ml of 10% Na ₂ S ₂ O ₅ and store sample at 6°C
22. Cyanide	✓	500 mL	Amber Glass, washed with pesticide grade acetone	Acidify to pH 2 with H ₂ SO ₄ Store sample at 6°C
23. Chemical oxygen demand (COD)	✓	150 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	Fill to full container without air gap; acidify to pH 2 with H ₂ SO ₄ and store sample at 6°C
24. Phenols	✓	500 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	Fill to full container without air gap; add 2 drops of 2M zinc acetate, adjust pH to 9 with 6M NaOH. Store sample at 6°C
25. *Formaldehyde		25 mL	PE, washed with pesticide grade Acetone;	Add 0.05 ml of 10% Na ₂ S ₂ O ₅ , acidify to pH 2 with H ₂ SO ₄ . Store sample at 6°C
26. Sulfide (Remark 5)	✓	50 mL	Amber Glass, washed with nitric acid, pre-add 6.5mL of 2M HNO ₃	PE, clean, sterile, non-reactive
27. Adsorbable organically bound halogens (AOX)	✓	100 mL	PE, clean, sterile, non-reactive	Foam higher than 45 cm (visual estimation): Yes / No
28. Total Coliform (Remark 6)	✓	125 mL		Add 1mL of 2.5% EDTA, 0.5g zinc acetate. Store sample at 6°C
29. Persistent foam	✓	N.A.		
30. Sulfite	✓	100 mL	Amber Glass, washed with pesticide grade acetone	
31. Total-N	✓	100 mL	Amber Glass with wide-mouth PTFE lid, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	Acidify to pH 2 with H ₂ SO ₄ Store sample at 6°C
32. Ammonium-N	✓	500 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	
33. Oil and Grease	✓	1000 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	
34. Total Hydrocarbon		1000 mL	Amber Glass, washed with nitric acid, pre-add 6.5 mL of 2M H ₂ SO ₄	
35. Luminescent Bacteria Toxicity		1000 mL	Amber Glass, washed with nitric acid, rinsed thoroughly with distilled water and dried before use	Without adding acid Store sample at 6°C
36. Sulphate		100 mL		
37. Chloride		100 mL		
38. Others:				

Observation/Remark:

*Remarks:

- Individual sampling can be performed upon request
- The minimum sampling time for 2016 ZDHC guideline is 6 hours with no more than one hour between discrete samples. Sampling time could be adjusted upon request.
- Scope of ZDHC guideline: Parameter 1, 2, 4-9, 12, 14-17, 19-24, 26-33
Scope of synthetic leather industry: Parameter 1, 2, 4-9, 12, 14-17, 19-33
Scope of MMCF: Parameter 4, 5, 17, 19-24, 26, 27, 31-37
Free primary aromatic amine, pesticides, nitrosamine and TDS are not in the scope of ZDHC Guideline, they are tested upon request.
- Refer to CPSD-AN-000019-STIP01, locations with those CPSD test capability inside TCD matrix can perform the combined test.
- Refer to CPSD-AN-000570-MTHD for additional pretreatment of sulfide if only dissolved sulfide is required to be tested.
- Refer to CPSD-AN-00613-MTHD for preparation of field blank for specific parameters.

Recorded by:

张菊明

Date: 2021.11.16

Comment from factory:

外埠后取样品 N34°24'33" E117°23'30"

Acknowledgement by factory:

I hereby confirmed that Bureau Veritas has completed the stated sampling activity at captioned date, time and location. All sample(s) is/are collected in designated container(s) and without any observation in leakage. Sample(s) collected by Bureau Veritas is/are stored in portable freezer / fridge that is maintained in 1-6°C

Signatory of Factory Representative:

Full Name:

时明

Date: 2021.11.16



Technical Report:

(6621)320-0353

November 29, 2020

Page 33 of 33

APPENDIX D/附录 D – Discharge License/排放标准

当前位置：水污染物排放信息审核

1、废水污染物排放许可限值

(1) 主要排放口

排放口编号	排放口名称	污染物种类	许可排放浓度限值 (mg/L)
DW001	废水排放口	可吸附有机卤化物	12mg/L
DW001	废水排放口	悬浮物	100mg/L
DW001	废水排放口	流量	/
DW001	废水排放口	色度	80
DW001	废水排放口	化学需氧量	200mg/L
DW001	废水排放口	五日生化需氧量	50mg/L
DW001	废水排放口	总氮 (以N计)	30mg/L
DW001	废水排放口	硫化物	0.5mg/L
DW001	废水排放口	pH值	6-9
DW001	废水排放口	二氧化氯	0.5mg/L
DW001	废水排放口	氨氮 (NH ₃ -N)	20mg/L
DW001	废水排放口	总磷 (以P计)	1.5mg/L
DW001	废水排放口	苯胺类	1.0mg/L
主要排放口合计			CODcr
			氨氮